


INDUSTRIAL COMPONENT DATA

ADXL0075600 LOVATO SOFT STARTER, ADXL... TYPE, WITH INTEGRATED BY-PASS RELAY. AUXILIARY SUPPLY 100...240VAC. R..

Brand: LOVATO ELECTRIC | Manufacturer Part Number: ADXL0075600



Manufacturer	LOVATO ELECTRIC
MPN / Reference	ADXL0075600
Catalog number	100240
Category	Soft starter
Minimum order	1 Pcs
Document ID	EO-20303B90EC
Generated	2026-08-05

Product Overview

SOFT STARTER, ADXL... TYPE, WITH INTEGRATED BY-PASS RELAY. AUXILIARY SUPPLY 100...240VAC. RATED OPERATIONAL VOLTAGE 208...600VAC, 75A

SOFT STARTER 75A 600V

Soft starter, ADXL... type, with integrated by-pass relay. Auxiliary supply 100...240VAC. Rated operational voltage 208...600VAC, 75A

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path LOVATO ELECTRIC > Soft Starters / Starters Static - LOVATO ELECTRIC

Additional Product Information

ADXL0075600

Soft starter, ADXL... type, with integrated by-pass relay. Auxiliary supply 100...240VAC. Rated operational voltage 208...600VAC, 75A

Technical specifications

Type of product:Advanced, two phase controlNumber of controlled phases:2Rated operational voltage:208...600VACRated supply voltage:100...240VACRated starter current I_e [A]:75Rated motor power 230VAC [kW]:22Rated motor power 400VAC [kW]:37Rated motor power 500VAC [kW]:45Functions:NFC, motor current thermal protection, starting with current limit, optical port, optional RS485, torque control, kick start, PTC input, event logOrder code ADXL0075600

Weight [g] 2920

Qty. per package 1
Multiple qty. of packs per order 1
Package dimensions [mm] 225X100X200
Volume [cm³] 4500
Bar code [EAN13] 8013975220269
HS Code 85044090
897.7 £
ETIM for ADXL0075600 Low-voltage industrial controls and switchgear (EC000640)
Feature Name
Feature Value
Voltage type for actuating (EF008242)
AC
Degree of protection (IP) (EF005474)
IP00
Function (EF000030)
Single direction
Rated control supply voltage AC 60 Hz (EF003979)
100 V
Rated control supply voltage AC 50 Hz (EF003978)
100 V
Rated operating voltage U_e (EF002418)
208 V
Torque control (EF009215)
Yes
Internal bypass (EF009214)
Yes
Integrated motor overload protection (EF007297)
Yes
With display (EF000458)
Yes
Rated surrounding temperature without derating (EF007074)
60 °C
Rated power three-phase motor, inline, at 400 V (EF007054)
37 kW
Rated power three-phase motor, inline, at 230 V (EF00...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LOVATO ELECTRIC / ADXL0075600 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.