

INDUSTRIAL COMPONENT DATA

KCN3L02 LOVATO LIMIT SWITCH, K SERIES, KEY OPERATED, 2 SIDE CABLE ENTRY. DIMENSIONS COMPATIBLE TO EN 50047, ..

Brand: LOVATO ELECTRIC | Manufacturer Part Number: KCN3L02



Manufacturer	LOVATO ELECTRIC
MPN / Reference	KCN3L02
Catalog number	10000
Category	End switch
Minimum order	1 Pcs
Document ID	EO-13D85D8760
Generated	2026-08-05

Product Overview

LIMIT SWITCH, K SERIES, KEY OPERATED, 2 SIDE CABLE ENTRY. DIMENSIONS COMPATIBLE TO EN 50047, PLASTIC BODY, CONTACTS 2NC SLOW BREAK. STRAIGHT "T" KEY

"STRAIGHT ""T"" KEY PLASTIC SAFE- TY SWI

Limit switch, K series, key operated, 2 side cable entry. Dimensions compatible to EN 50047, plastic body, contacts 2NC slow action. Straight "T" key

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	LOVATO ELECTRIC > Limit, micro and foot switches - LOVATO ELECTRIC
--------------	--

Additional Product Information

KCN3L02

Limit switch, K series, key operated, 2 side cable entry. Dimensions compatible to EN 50047, plastic body, contacts 2NC slow action. Straight "T" key

Technical specifications

Type of product:Safety limit switchesProduct characteristics:Key operatedHousing material:Polymer thermoplasticKey shape:Straight "T"Cable entry:M20 on the sidesType of contacts:2NC Slow actionOrder code KCN3L02

Weight [g] 106

Qty. per package 1

Multiple qty. of packs per order 1

Package dimensions [mm] 065X046X090

Volume [cm³] 269.1

Bar code [EAN13] 8013975127803

HS Code 85365080

70.85 £

ETIM for KCN3L02 Sensors (EC000030)

Feature Name

Feature Value

Alignment of the control element (EF008793)

Other

Type of interface (EF006977)

None

Type of control element (EF006976)

Other

Degree of protection (IP) (EF005474)

IP65

Construction type housing (EF004008)

Cuboid

Explosion safety category for dust (EF003998)

None

Explosion safety category for gas (EF003997)

None

Type of electric connection (EF003961)

Cable entry metrical

Type of interface for safety communication (EF003956)

None

Coating housing (EF001601)

Other

Housing material (EF001596)

Plastic

Switching function (EF000189)

Slow-action switch

Ambient temperature during operating (EF007515)

-25 °C

Switching function latching (EF007447)

No

Output electronic (EF006987)

No

Forced opening (EF006694)

Yes

With status indication (EF001602)

No

Suitable for safety functions (EF001597)

Yes

Number of contacts as change-over contact (EF008257)

0

Number of contac...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LOVATO ELECTRIC / KCN3L02 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.