

INDUSTRIAL COMPONENT DATA

SA21PA320R LOVATO SURGE PROTECTION DEVICE TYPE 2 WITH PLUG-IN CARTRIDGE, IEC MAXIMUM DISCHARGE CURRENT I_{MAX} ..

Brand: LOVATO ELECTRIC | Manufacturer Part Number: SA21PA320R



Manufacturer	LOVATO ELECTRIC
MPN / Reference	SA21PA320R
Catalog number	10000
Category	Surge protection device for power supply systems
Minimum order	1 Pcs
Document ID	EO-859CD3706C
Generated	2026-08-02

Product Overview

SURGE PROTECTION DEVICE TYPE 2 WITH PLUG-IN CARTRIDGE, IEC MAXIMUM DISCHARGE CURRENT I_{MAX} (8/20^μS) 40KA PER POLE, 1P. WITH CONTACT REMOTE

Surge protection device type 2 with plug-in cartridge, IEC maximum discharge current I_{max} (8/20^μs) 40kA per pole, 1P. With remote contact

TYPE 2 REMOVABLE CARTRIDGE SURGE ARRESTER, MAXIMUM DISCHARGE CURRENT I_{MAX} (8/20^μ S) 40KA PER POLE, 1P. WITH REMOTE CONTACT

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path LOVATO ELECTRIC > Surge protection devices - LOVATO ELECTRIC

Additional Product Information

SA21PA320R

Surge protection device type 2 with plug-in cartridge, IEC maximum discharge current I_{max} (8/20^μs) 40kA per pole, 1P.

With remote contact

Technical specifications

Type of product:SPDOrder code SA21PA320R

Weight [g] 160

Qty. per package 1

Multiple qty. of packs per order 1

Package dimensions [mm] 109X023X078

Volume [cm³] 195.574

Bar code [EAN13] 8013975191637

HS Code 85365080

ETIM for SA21PA320R Earthing, lightning and surge protection (EC000941)

Feature Name

Feature Value

Degree of protection (IP) (EF005474)

IP20

Signalling at the device (EF004241)

Optic

Construction size (EF002566)

1 modular spacing

Mounting method (EF000003)

DIN rail (top hat rail) 35 mm

Leakage-current free (EF016002)

No

Integrated short-circuit protection (EF016000)

No

System configuration TN-C-S (EF009933)

No

System configuration other (EF009932)

No

System configuration TT (EF009931)

No

System configuration TN-S (EF009930)

Yes

System configuration TN-C (EF009929)

No

System configuration TN (EF009928)

No

System configuration IT (EF009927)

No

System configuration DC (EF009926)

No

Integrated backup fuse (EF008797)

No

Category type 2 (EF004230)

Yes

With remote signalling contact (EF000422)

Yes

Max. discharge surge current (8/20) (EF012274)

40 kA

Max. conductor cross section flexible (fine-strand) (EF008828)

25 mm²

Max. conductor cross section solid (solid, stranded) (EF008827)

35 mm²

Voltage protection level L-N (EF004236)

1500 kV

Nominal voltage AC (EF004220)

230 V

Nominal discharge surge curren...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LOVATO ELECTRIC / SA21PA320R with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.