

## INDUSTRIAL COMPONENT DATA

# 11BGP0901D024 BGP0901D024 LOVATO THREE-POLE CONTACTOR, IEC OPERATING CURRENT IE (AC3) 9A, DC COIL, 24VDC, 1N..

Brand: LOVATO ELECTRIC | Manufacturer Part Number: 11BGP0901D024



|                 |                               |
|-----------------|-------------------------------|
| Manufacturer    | LOVATO ELECTRIC               |
| MPN / Reference | 11BGP0901D024                 |
| Catalog number  | BGP0901D024                   |
| Category        | Power contactor, AC switching |
| Minimum order   | 1 Pcs                         |
| Document ID     | EO-791F201E1C                 |
| Generated       | 2026-08-02                    |

## Product Overview

THREE-POLE CONTACTOR, IEC OPERATING CURRENT IE (AC3) = 9A, DC COIL, 24VDC, 1NC AUXILIARY CONTACT, REAR PCB SOLDER PIN

Minicont 3P 9A AC3 1NC 24V DC Printed Circuit

Three-pole contactor, IEC operating current Ie (AC3) = 9A, DC coil, 24VDC, 1NC auxiliary contact, rear PCB solder pin

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                                                           |
|--------------|---------------------------------------------------------------------------|
| Catalog path | LOVATO ELECTRIC > Industrial Contactors and Accessories - LOVATO ELECTRIC |
|--------------|---------------------------------------------------------------------------|

## Additional Product Information

11BGP0901D024

Three-pole contactor, IEC operating current Ie (AC3) = 9A, DC coil, 24VDC, 1NC auxiliary contact, rear PCB solder pin  
Technical specifications

Type of product:ContactorsNumber of poles:3Type of coil:DC coilRated coil voltage [V]:24IEC operating current Ith (AC1) [A]:20IEC operating current and power Ie (AC3) 400V [A/Kw]:9A / 4.0KwUL/CSA horsepower ratings 480V [HP]:5Type of built-in auxiliary contacts:1NCType of mounting:Screw / DIN rail 35mmOrder code 11BGP0901D024

Weight [g] 243

Qty. per package 1

Multiple qty. of packs per order 1

Package dimensions [mm] 060X045X070

Volume [cm<sup>3</sup>] 189  
Bar code [EAN13] 8013975144923  
HS Code 85365080  
65.75 £  
ETIM for 11BGP0901D024 Low-voltage industrial controls and switchgear (EC000066)  
Feature Name  
Feature Value  
Voltage type for actuating (EF008242)  
DC  
Type of electrical connection of main circuit (EF006819)  
PCB connection  
Rated control supply voltage DC (EF003980)  
24 V  
Modular version (EF001126)  
No  
Rated operation current I<sub>e</sub> at AC-4, 400 V (EF008495)  
4 A  
Rated operation current I<sub>e</sub> at AC-1, 400 V (EF001393)  
20 A  
Rated operation current I<sub>e</sub> at AC-3, 400 V (EF001392)  
9 A  
Number of auxiliary contacts as normally closed contact (EF001377)  
1  
Number of auxiliary contacts as normally open contact (EF001376)  
0  
Number of normally closed contacts as main contact (EF001375)  
0  
Number of normally open contacts as main contact (EF001374)  
3  
Rated operation power at AC-3, 400 V (EF001364)  
4 kW

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LOVATO ELECTRIC / 11BGP0901D024 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.