

## INDUSTRIAL COMPONENT DATA

**BF0901L024 LOVATO THREE-POLE CONTACTOR, IEC  
OPERATING CURRENT IE (AC3) 9A, DC COIL LOW  
CONSUMPTION, 24VDC, 1..**

Brand: LOVATO ELECTRIC | Manufacturer Part Number: BF0901L024



|                 |                               |
|-----------------|-------------------------------|
| Manufacturer    | LOVATO ELECTRIC               |
| MPN / Reference | BF0901L024                    |
| Catalog number  | 10000                         |
| Category        | Power contactor, AC switching |
| Minimum order   | 1 Pcs                         |
| Document ID     | EO-1CB859353F                 |
| Generated       | 2026-08-04                    |

**Product Overview**

THREE-POLE CONTACTOR, IEC OPERATING CURRENT IE (AC3) = 9A, DC COIL LOW CONSUMPTION, 24VDC, 1NC  
AUXILIARY CONTACT

3P CONTACTOR 1NC 9A AC3 24VDC LOW C.

Three-pole contactor, IEC operating current Ie (AC3) = 9A, DC coil low consumption, 24VDC, 1NC auxiliary contact with  
mirror contact function

## STRUCTURED PRODUCT DATA

**Technical Specifications**

No structured technical attributes are currently available. Submit an RFQ for technical review.

**Classification & Catalog Path**

|              |                                                                           |
|--------------|---------------------------------------------------------------------------|
| Catalog path | LOVATO ELECTRIC > Industrial Contactors and Accessories - LOVATO ELECTRIC |
|--------------|---------------------------------------------------------------------------|

**Additional Product Information**

BF0901L024

Three-pole contactor, IEC operating current Ie (AC3) = 9A, DC coil low consumption, 24VDC, 1NC auxiliary contact with  
mirror contact function

Technical specifications

Type of product:ContactorsNumber of poles:3Type of coil:DC coil low consumptionRated coil voltage [V]:24IEC operating  
current Ith (AC1) [A]:25IEC operating current and power Ie (AC3) 400V [A/Kw]:9A / 4.2KwUL/CSA horsepower ratings 480V  
[HP]:5Type of built-in auxiliary contacts:1NCType of mounting:Screw / DIN rail 35mmOrder code BF0901L024

Weight [g] 502

Qty. per package 1

Multiple qty. of packs per order 1  
Package dimensions [mm] 093X048X110  
Volume [cm<sup>3</sup>] 491.04  
Bar code [EAN13] 8013975168103  
HS Code 85365080  
82.22 £  
ETIM for BF0901L024 Low-voltage industrial controls and switchgear (EC000066)  
Feature Name  
Feature Value  
Voltage type for actuating (EF008242)  
DC  
Type of electrical connection of main circuit (EF006819)  
Screw connection  
Rated control supply voltage DC (EF003980)  
24 V  
Modular version (EF001126)  
No  
Rated operation current I<sub>e</sub> at AC-4, 400 V (EF008495)  
4.9 A  
Rated operation current I<sub>e</sub> at AC-1, 400 V (EF001393)  
25 A  
Rated operation current I<sub>e</sub> at AC-3, 400 V (EF001392)  
9 A  
Number of auxiliary contacts as normally closed contact (EF001377)  
1  
Number of auxiliary contacts as normally open contact (EF001376)  
0  
Number of normally closed contacts as main contact (EF001375)  
0  
Number of normally open contacts as main contact (EF001374)  
3  
Rated operation power at AC-3, 400 V (EF001364)  
4.2 kW

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LOVATO ELECTRIC / BF0901L024 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.