

INDUSTRIAL COMPONENT DATA

11BGF0901L024 BGF0901L024 LOVATO THREE-POLE CONTACTOR, IEC OPERATING CURRENT IE (AC3) 9A, DC COIL LOW CONSUM..

Brand: LOVATO ELECTRIC | Manufacturer Part Number: 11BGF0901L024



Manufacturer	LOVATO ELECTRIC
MPN / Reference	11BGF0901L024
Catalog number	BGF0901L024
Category	Power contactor, AC switching
Minimum order	1 Pcs
Document ID	EO-149AB9D761
Generated	2026-08-04

Product Overview

THREE-POLE CONTACTOR, IEC OPERATING CURRENT IE (AC3) = 9A, DC COIL LOW CONSUMPTION, 24VDC, 1NC AUXILIARY CONTACT, FASTON TERMINALS

Minicont. 3P 9A AC3 1 aux NC 24V DC Faston b. consumption

Three-pole contactor, IEC operating current Ie (AC3) = 9A, DC coil low consumption, 24VDC, 1NC auxiliary contact, Faston terminals

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	LOVATO ELECTRIC > Industrial Contactors and Accessories - LOVATO ELECTRIC
--------------	---

Additional Product Information

11BGF0901L024

Three-pole contactor, IEC operating current Ie (AC3) = 9A, DC coil low consumption, 24VDC, 1NC auxiliary contact, Faston terminals

Technical specifications

Type of product: Contactors
Number of poles: 3
Type of coil: DC coil low consumption
Rated coil voltage [V]: 24
IEC operating current Ith (AC1) [A]: 20
IEC operating current and power Ie (AC3) 400V [A/Kw]: 9A / 4.0Kw
UL/CSA horsepower ratings 480V [HP]: 5
Type of built-in auxiliary contacts: 1NC
Type of mounting: Screw / DIN rail 35mm
Order code 11BGF0901L024

Weight [g] 224

Qty. per package 1

Multiple qty. of packs per order 1
Package dimensions [mm] 060X045X060
Volume [cm³] 162
Bar code [EAN13] 8013975121177
HS Code 85365080
72.61 £
ETIM for 11BGF0901L024 Low-voltage industrial controls and switchgear (EC000066)
Feature Name
Feature Value
Voltage type for actuating (EF008242)
DC
Type of electrical connection of main circuit (EF006819)
Flat plug-in connection
Rated control supply voltage DC (EF003980)
24 V
Modular version (EF001126)
No
Rated operation current I_e at AC-4, 400 V (EF008495)
4 A
Rated operation current I_e at AC-1, 400 V (EF001393)
20 A
Rated operation current I_e at AC-3, 400 V (EF001392)
9 A
Number of auxiliary contacts as normally closed contact (EF001377)
1
Number of auxiliary contacts as normally open contact (EF001376)
0
Number of normally closed contacts as main contact (EF001375)
0
Number of normally open contacts as main contact (EF001374)
3
Rated operation power at AC-3, 400 V (EF001364)
4 kW

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LOVATO ELECTRIC / 11BGF0901L024 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.