

INDUSTRIAL COMPONENT DATA

KMB1L03 LOVATO LIMIT SWITCH, K SERIES, TOP ROLLER PUSH PLUNGER, 1 BOTTOM CABLE ENTRY. DIMENSIONS TO EN 50047..

Brand: LOVATO ELECTRIC | Manufacturer Part Number: KMB1L03



Manufacturer	LOVATO ELECTRIC
MPN / Reference	KMB1L03
Catalog number	10000
Category	End switch
Minimum order	1 Pcs
Document ID	EO-9588CD1BA6
Generated	2026-08-02

Product Overview

LIMIT SWITCH, K SERIES, TOP ROLLER PUSH PLUNGER, 1 BOTTOM CABLE ENTRY. DIMENSIONS TO EN 50047, METAL BODY, CONTACTS 3NC SLOW BREAK. PLASTIC ROLLER

TOP PLUNGER METAL LIMIT SWITCH 3NC

Limit switch, K series, top roller push plunger, 1 bottom cable entry. Dimensions to EN 50047, metal body, contacts 3NC slow action. Plastic roller

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	LOVATO ELECTRIC > Limit, micro and foot switches - LOVATO ELECTRIC
--------------	--

Additional Product Information

KMB1L03

Limit switch, K series, top roller push plunger, 1 bottom cable entry. Dimensions to EN 50047, metal body, contacts 3NC slow action. Plastic roller

Technical specifications

Type of product: Metal and plastic limit switches Product characteristics: Top roller push plunger Housing

material: Aluminium-zinc alloy Roller material: Plastic Type of contacts: 3NC Slow action Cable entry: M20 on the sides Order code KMB1L03

Weight [g] 158

Qty. per package 1

Multiple qty. of packs per order 1
Package dimensions [mm] 100X044X032
Volume [cm³] 140.8
Bar code [EAN13] 8013975115619
HS Code 85365080
56.12 £
ETIM for KMB1L03 Sensors (EC000030)
Feature Name
Feature Value
Alignment of the control element (EF008793)
Roller cam straight
Type of interface (EF006977)
None
Type of control element (EF006976)
Roller cam
Degree of protection (IP) (EF005474)
IP65
Construction type housing (EF004008)
Cuboid
Explosion safety category for dust (EF003998)
None
Explosion safety category for gas (EF003997)
None
Type of electric connection (EF003961)
Cable entry metrical
Type of interface for safety communication (EF003956)
None
Coating housing (EF001601)
Powder coated
Housing material (EF001596)
Metal
Switching function (EF000189)
Slow-action switch
Ambient temperature during operating (EF007515)
-25 °C
Switching function latching (EF007447)
No
Output electronic (EF006987)
No
Forced opening (EF006694)
Yes
With status indication (EF001602)
No
Suitable for safety functions (EF001597)
No
Number of contacts as chang...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LOVATO ELECTRIC / KMB1L03 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.