

INDUSTRIAL COMPONENT DATA

KBM2A11 LOVATO LIMIT SWITCH, K SERIES, WOBBLE STICK, OMNIDIRECTIONAL, 1 BOTTOM CABLE ENTRY. DIMENSIONS TO EN..

Brand: LOVATO ELECTRIC | Manufacturer Part Number: KBM2A11



Manufacturer	LOVATO ELECTRIC
MPN / Reference	KBM2A11
Catalog number	10000
Category	End switch
Minimum order	1 Pcs
Document ID	EO-9504AD49DC
Generated	2026-08-03

Product Overview

LIMIT SWITCH, K SERIES, WOBBLE STICK, OMNIDIRECTIONAL, 1 BOTTOM CABLE ENTRY. DIMENSIONS TO EN 50047, PLASTIC BODY, CONTACTS 1NO+1NC SLOW BREAK MAKE BEFORE BREAK. SEMIRIGID ROD

WOBBLE STICK OMND 1NO+1NC SLOW BREAK

Limit switch, K series, wobble stick, omnidirectional, 1 bottom cable entry. Dimensions to EN 50047, plastic body, contacts 1NO+1NC slow action make before break. Semirigid rod

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	LOVATO ELECTRIC > Limit, micro and foot switches - LOVATO ELECTRIC
--------------	--

Additional Product Information

KBM2A11

Limit switch, K series, wobble stick, omnidirectional, 1 bottom cable entry. Dimensions to EN 50047, plastic body, contacts 1NO+1NC slow action make before break. Semirigid rod

Technical specifications

Type of product: Metal and plastic limit switches
Product characteristics: Wobble stick, omnidirectional
Housing material: Polymer thermoplastic
Rod characteristics: Semirigid
Type of contacts: 1NO+1NC Slow action make before break
Cable entry: M20 on the bottom
Order code KBM2A11

Weight [g] 89

Qty. per package 1

Multiple qty. of packs per order 1
Package dimensions [mm] 216X041X044
Volume [cm³] 389.664
Bar code [EAN13] 8013975115114
HS Code 85365080
35.34 £
ETIM for KBM2A11 Sensors (EC000030)
Feature Name
Feature Value
Alignment of the control element (EF008793)
Other
Type of interface (EF006977)
None
Type of control element (EF006976)
Spring-rod
Degree of protection (IP) (EF005474)
IP65
Construction type housing (EF004008)
Cuboid
Explosion safety category for dust (EF003998)
None
Explosion safety category for gas (EF003997)
None
Type of electric connection (EF003961)
Cable entry metrical
Type of interface for safety communication (EF003956)
None
Coating housing (EF001601)
Other
Housing material (EF001596)
Plastic
Switching function (EF000189)
Slow-action switch with overlapping
Ambient temperature during operating (EF007515)
-25 °C
Switching function latching (EF007447)
No
Output electronic (EF006987)
No
Forced opening (EF006694)
Yes
With status indication (EF001602)
No
Suitable...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LOVATO ELECTRIC / KBM2A11 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.