

INDUSTRIAL COMPONENT DATA

KBM2L20 LOVATO LIMIT SWITCH, K SERIES, WOBBLE STICK, OMNIDIRECTIONAL, 1 BOTTOM CABLE ENTRY. DIMENSIONS TO EN..

Brand: LOVATO ELECTRIC | Manufacturer Part Number: KBM2L20



Manufacturer	LOVATO ELECTRIC
MPN / Reference	KBM2L20
Catalog number	10000
Category	End switch
Minimum order	1 Pcs
Document ID	EO-711DF3D487
Generated	2026-08-02

Product Overview

LIMIT SWITCH, K SERIES, WOBBLE STICK, OMNIDIRECTIONAL, 1 BOTTOM CABLE ENTRY. DIMENSIONS TO EN 50047, PLASTIC BODY, CONTACTS 2NO SLOW BREAK. SEMIRIGID ROD

WOBBLE STICK OMND 2NO SLOW BREAK

Limit switch, K series, wobble stick, omnidirectional, 1 bottom cable entry. Dimensions to EN 50047, plastic body, contacts 2NO slow action. Semirigid rod

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	LOVATO ELECTRIC > Limit, micro and foot switches - LOVATO ELECTRIC
--------------	--

Additional Product Information

KBM2L20

Limit switch, K series, wobble stick, omnidirectional, 1 bottom cable entry. Dimensions to EN 50047, plastic body, contacts 2NO slow action. Semirigid rod

Technical specifications

Type of product: Metal and plastic limit switches
Product characteristics: Wobble stick, omnidirectional
Housing material: Polymer thermoplastic
Rod characteristics: Semirigid
Type of contacts: 2NO Slow action
Cable entry: M20 on the bottom
Order code KBM2L20

Weight [g] 90

Qty. per package 1

Multiple qty. of packs per order 1
Package dimensions [mm] 216X041X044
Volume [cm³] 389.664
Bar code [EAN13] 8013975115169
HS Code 85365080
37.27 £
ETIM for KBM2L20 Sensors (EC000030)
Feature Name
Feature Value
Alignment of the control element (EF008793)
Other
Type of interface (EF006977)
None
Type of control element (EF006976)
Spring-rod
Degree of protection (IP) (EF005474)
IP65
Construction type housing (EF004008)
Cuboid
Explosion safety category for dust (EF003998)
None
Explosion safety category for gas (EF003997)
None
Type of electric connection (EF003961)
Cable entry metrical
Type of interface for safety communication (EF003956)
None
Coating housing (EF001601)
Other
Housing material (EF001596)
Plastic
Switching function (EF000189)
Slow-action switch
Ambient temperature during operating (EF007515)
-25 °C
Switching function latching (EF007447)
No
Output electronic (EF006987)
No
Forced opening (EF006694)
Yes
With status indication (EF001602)
No
Suitable for safety functions (EF001597)
No
Number of contacts as cha...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LOVATO ELECTRIC / KBM2L20 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.