

## INDUSTRIAL COMPONENT DATA

# KNM1A11 LOVATO LIMIT SWITCH, K SERIES, WOBBLE STICK, OMNIDIRECTIONAL, 2 SIDE CABLE ENTRY. DIMENSIONS COMPATI..

Brand: LOVATO ELECTRIC | Manufacturer Part Number: KNM1A11



|                 |                 |
|-----------------|-----------------|
| Manufacturer    | LOVATO ELECTRIC |
| MPN / Reference | KNM1A11         |
| Catalog number  | 10000           |
| Category        | End switch      |
| Minimum order   | 1 Pcs           |
| Document ID     | EO-14FEA0DE4B   |
| Generated       | 2026-08-06      |

## Product Overview

LIMIT SWITCH, K SERIES, WOBBLE STICK, OMNIDIRECTIONAL, 2 SIDE CABLE ENTRY. DIMENSIONS COMPATIBLE TO EN 50047, METAL BODY, CONTACTS 1NO+1NC SLOW BREAK MAKE BEFORE BREAK. FLEXIBLE ROD WOBBLE STICK OMNID 2 ENTRIES L/S 1NO+1NC

Limit switch, K series, wobble stick, omnidirectional, 2 side cable entry. Dimensions compatible to EN 50047, metal body, contacts 1NO+1NC slow action make before break. Flexible rod

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                                                    |
|--------------|--------------------------------------------------------------------|
| Catalog path | LOVATO ELECTRIC > Limit, micro and foot switches - LOVATO ELECTRIC |
|--------------|--------------------------------------------------------------------|

## Additional Product Information

KNM1A11

Limit switch, K series, wobble stick, omnidirectional, 2 side cable entry. Dimensions compatible to EN 50047, metal body, contacts 1NO+1NC slow action make before break. Flexible rod

Technical specifications

Type of product: Metal and plastic limit switches  
Product characteristics: Wobble stick, omnidirectional  
Housing material: Aluminium-zinc alloy  
Rod characteristics: Flexible  
Type of contacts: 1NO+1NC  
Slow action make before break  
Cable entry: M20 on the sides  
Order code KNM1A11

Weight [g] 240

Qty. per package 1

Multiple qty. of packs per order 1  
Package dimensions [mm] 185X041X085  
Volume [cm<sup>3</sup>] 644.725  
Bar code [EAN13] 8013975128916  
HS Code 85365080  
50.13 £  
ETIM for KNM1A11 Sensors (EC000030)  
Feature Name  
Feature Value  
Alignment of the control element (EF008793)  
Other  
Type of interface (EF006977)  
None  
Type of control element (EF006976)  
Spring-rod  
Degree of protection (IP) (EF005474)  
IP65  
Construction type housing (EF004008)  
Cuboid  
Explosion safety category for dust (EF003998)  
None  
Explosion safety category for gas (EF003997)  
None  
Type of electric connection (EF003961)  
Cable entry metrical  
Type of interface for safety communication (EF003956)  
None  
Coating housing (EF001601)  
Powder coated  
Housing material (EF001596)  
Metal  
Switching function (EF000189)  
Slow-action switch with overlapping  
Ambient temperature during operating (EF007515)  
-25 °C  
Switching function latching (EF007447)  
No  
Output electronic (EF006987)  
No  
Forced opening (EF006694)  
Yes  
With status indication (EF001602)  
N...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LOVATO ELECTRIC / KNM1A11 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.