

INDUSTRIAL COMPONENT DATA

KNM2L11 LOVATO LIMIT SWITCH, K SERIES, WOBBLE STICK, OMNIDIRECTIONAL, 2 SIDE CABLE ENTRY. DIMENSIONS COMPATI..

Brand: LOVATO ELECTRIC | Manufacturer Part Number: KNM2L11



Manufacturer	LOVATO ELECTRIC
MPN / Reference	KNM2L11
Catalog number	10000
Category	End switch
Minimum order	1 Pcs
Document ID	EO-F09435B87F
Generated	2026-08-05

Product Overview

LIMIT SWITCH, K SERIES, WOBBLE STICK, OMNIDIRECTIONAL, 2 SIDE CABLE ENTRY. DIMENSIONS COMPATIBLE TO EN 50047, METAL BODY, CONTACTS 1NO+1NC SLOW BREAK. SEMIRIGID ROD

WOBBLE STICK OMNID 2 ENTRIES L/S 1NO+1NC

Limit switch, K series, wobble stick, omnidirectional, 2 side cable entry. Dimensions compatible to EN 50047, metal body, contacts 1NO+1NC slow action. Semirigid rod

K SERIES LIMIT SWITCH, OMNIDIRECTIONAL STEM, 2 SIDE CABLE ENTRIES. EN 50047 COMPATIBLE DIMENSIONS, METAL HOUSING, SLOW 1NO+1NC CONTACTS. SEMI-RIGID SHAFT

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	LOVATO ELECTRIC > Limit, micro and foot switches - LOVATO ELECTRIC
--------------	--

Additional Product Information

KNM2L11

Limit switch, K series, wobble stick, omnidirectional, 2 side cable entry. Dimensions compatible to EN 50047, metal body, contacts 1NO+1NC slow action. Semirigid rod

Technical specifications

Type of product: Metal and plastic limit switches Product characteristics: Wobble stick, omnidirectional Housing

material: Aluminium-zinc alloy Rod characteristics: Semirigid Type of contacts: 1NO+1NC Slow action Cable entry: M20 on the sides Order code KNM2L11

Weight [g] 230
Qty. per package 1
Multiple qty. of packs per order 1
Package dimensions [mm] 185X041X085
Volume [cm³] 644.725
Bar code [EAN13] 8013975128985
HS Code 85365080
47.57 £
ETIM for KNM2L11 Sensors (EC000030)
Feature Name
Feature Value
Alignment of the control element (EF008793)
Other
Type of interface (EF006977)
None
Degree of protection (IP) (EF005474)
IP65
Construction type housing (EF004008)
Cuboid
Explosion safety category for dust (EF003998)
None
Explosion safety category for gas (EF003997)
None
Type of electric connection (EF003961)
Cable entry metrical
Type of interface for safety communication (EF003956)
None
Coating housing (EF001601)
Powder coated
Housing material (EF001596)
Metal
Switching function (EF000189)
Slow-action switch
Ambient temperature during operating (EF007515)
-25 °C
Switching function latching (EF007447)
No
Output electronic (EF006987)
No
Forced opening (EF006694)
Yes
With status indication (EF001602)
No
Suitable for safety functions (EF001597)
No
Number of contacts as change-over contact (EF008257...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LOVATO ELECTRIC / KNM2L11 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.