

INDUSTRIAL COMPONENT DATA

KCM2L20 LOVATO LIMIT SWITCH, K SERIES, WOBBLE STICK, OMNIDIRECTIONAL, 2 SIDE CABLE ENTRY. DIMENSIONS COMPATI..

Brand: LOVATO ELECTRIC | Manufacturer Part Number: KCM2L20



Manufacturer	LOVATO ELECTRIC
MPN / Reference	KCM2L20
Catalog number	10000
Category	End switch
Minimum order	1 Pcs
Document ID	EO-27EB829EBF
Generated	2026-08-04

Product Overview

LIMIT SWITCH, K SERIES, WOBBLE STICK, OMNIDIRECTIONAL, 2 SIDE CABLE ENTRY. DIMENSIONS COMPATIBLE TO EN 50047, PLASTIC BODY, CONTACTS 2NO SLOW BREAK. SEMIRIGID ROD

WOBBLE STICK OMNID 2 ENTRIES L/S 2NO

Limit switch, K series, wobble stick, omnidirectional, 2 side cable entry. Dimensions compatible to EN 50047, plastic body, contacts 2NO slow action. Semirigid rod

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	LOVATO ELECTRIC > Limit, micro and foot switches - LOVATO ELECTRIC
--------------	--

Additional Product Information

KCM2L20

Limit switch, K series, wobble stick, omnidirectional, 2 side cable entry. Dimensions compatible to EN 50047, plastic body, contacts 2NO slow action. Semirigid rod

Technical specifications

Type of product: Metal and plastic limit switches
Product characteristics: Wobble stick, omnidirectional
Housing material: Polymer thermoplastic
Rod characteristics: Semirigid
Type of contacts: 2NO Slow action
Cable entry: M20 on the sides
Order code KCM2L20

Weight [g] 106

Qty. per package 1

Multiple qty. of packs per order 1
Package dimensions [mm] 185X041X085
Volume [cm³] 644.725
Bar code [EAN13] 8013975127742
HS Code 85365080
40.76 £
ETIM for KCM2L20 Sensors (EC000030)
Feature Name
Feature Value
Alignment of the control element (EF008793)
Other
Type of interface (EF006977)
None
Type of control element (EF006976)
Spring-rod
Degree of protection (IP) (EF005474)
IP65
Construction type housing (EF004008)
Cuboid
Explosion safety category for dust (EF003998)
None
Explosion safety category for gas (EF003997)
None
Type of electric connection (EF003961)
Cable entry metrical
Type of interface for safety communication (EF003956)
None
Coating housing (EF001601)
Other
Housing material (EF001596)
Plastic
Switching function (EF000189)
Slow-action switch
Ambient temperature during operating (EF007515)
-25 °C
Switching function latching (EF007447)
No
Output electronic (EF006987)
No
Forced opening (EF006694)
Yes
With status indication (EF001602)
No
Suitable for safety functions (EF001597)
No
Number of contac...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LOVATO ELECTRIC / KCM2L20 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.