

INDUSTRIAL COMPONENT DATA

KNM1L20 LOVATO LIMIT SWITCH, K SERIES, WOBBLE STICK, OMNIDIRECTIONAL, 2 SIDE CABLE ENTRY. DIMENSIONS COMPATI..

Brand: LOVATO ELECTRIC | Manufacturer Part Number: KNM1L20



Manufacturer	LOVATO ELECTRIC
MPN / Reference	KNM1L20
Catalog number	10000
Category	End switch
Minimum order	1 Pcs
Document ID	EO-28964A34DA
Generated	2026-08-04

Product Overview

LIMIT SWITCH, K SERIES, WOBBLE STICK, OMNIDIRECTIONAL, 2 SIDE CABLE ENTRY. DIMENSIONS COMPATIBLE TO EN 50047, METAL BODY, CONTACTS 2NO SLOW BREAK. FLEXIBLE ROD

WOBBLE STICK OMNID 2 ENTRIES L/S 2NO

Limit switch, K series, wobble stick, omnidirectional, 2 side cable entry. Dimensions compatible to EN 50047, metal body, contacts 2NO slow action. Flexible rod

K SERIES LIMIT SWITCH, OMNIDIRECTIONAL STEM, 2 SIDE CABLE ENTRIES. EN 50047 COMPATIBLE DIMENSIONS, METAL HOUSING, SLOW 2NO CONTACTS. FLEXIBLE ROD

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	LOVATO ELECTRIC > Limit, micro and foot switches - LOVATO ELECTRIC
--------------	--

Additional Product Information

KNM1L20

Limit switch, K series, wobble stick, omnidirectional, 2 side cable entry. Dimensions compatible to EN 50047, metal body, contacts 2NO slow action. Flexible rod

Technical specifications

Type of product: Metal and plastic limit switches
Product characteristics: Wobble stick, omnidirectional
Housing material: Aluminium-zinc alloy
Rod characteristics: Flexible
Type of contacts: 2NO Slow action
Cable entry: M20 on the sides
Order code KNM1L20

Weight [g] 240
Qty. per package 1
Multiple qty. of packs per order 1
Package dimensions [mm] 185X041X085
Volume [cm³] 644.725
Bar code [EAN13] 8013975128947
HS Code 85365080
52.24 £
ETIM for KNM1L20 Sensors (EC000030)
Feature Name
Feature Value
Alignment of the control element (EF008793)
Other
Type of interface (EF006977)
None
Type of control element (EF006976)
Spring-rod
Degree of protection (IP) (EF005474)
IP65
Construction type housing (EF004008)
Cuboid
Explosion safety category for dust (EF003998)
None
Explosion safety category for gas (EF003997)
None
Type of electric connection (EF003961)
Cable entry metrical
Type of interface for safety communication (EF003956)
None
Coating housing (EF001601)
Powder coated
Housing material (EF001596)
Metal
Switching function (EF000189)
Slow-action switch
Ambient temperature during operating (EF007515)
-25 °C
Switching function latching (EF007447)
No
Output electronic (EF006987)
No
Forced opening (EF006694)
Yes
With status indication (EF001602)
No
Suitable for safety functions (EF001597)
No

Number of conta...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LOVATO ELECTRIC / KNM1L20 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.