

INDUSTRIAL COMPONENT DATA

PB-360P-48 MEANWELL AC-DC Single Output battery charger with PFC, Input with 3 pin IEC320-C14 socket, Output..

Brand: MEANWELL | Manufacturer Part Number: PB-360P-48



Manufacturer	MEANWELL
MPN / Reference	PB-360P-48
Catalog number	PB-360P-48
Category	CHARGERS
Minimum order	1 unit
Document ID	EO-8F541C61ED
Generated	2026-08-04

Product Overview

PB-360P-48 MEANWELL AC-DC Single Output battery charger with PFC, Input with 3 pin IEC320-C14 socket, Output..

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path MEANWELL > CHARGERS > PB

Additional Product Information

Name PB-360P-48

Long Description Battery charger for Gel, AGM and wet with PFC.

Load in 3 stages.

Format metal box.

Input range selectable by switch,90-132Vca/180-264vac. 47-63Hz.

Absorption voltage57,6 Vdc.

Float voltageFor 54.4 Vdc. Adjustable by potentiometer (52-58,6V).

Intensity of continuous load6,25 To.

Power:360W.

Type of batteries:Gel, AGM and wet.

Battery capacity:20-65Ah.

Efficiency typical:87%.

Factor corrector, power>0,65to 230vac at full load.

2-colour LED charging status indicator.

Working temperature: from-20up+60 ° Cof ambient temperature. Consult the technical data sheet to see the curves of drift.

Dimensions (Length x Width x Height) [mm]:253 x 135 x 48,5.

3 years of warranty.

Manufacturer: MEAN WELL.

The PB series are battery chargers for lead, Gel, AGM and wet. The type of cargo is carried out in 3 stages. Have input connector europeanIEC320-C14and output connector for screw.

Country of Origin Taiwan

Stock Yes

Manufacturer MEAN WELL

Product type Chargers

Format Box

Subformato Grid

Applications Industrial, Solar, Telecommunications

Series PB-360P

Warranty (Years) 3,00

Height (mm) 48.00

Width (mm) 135.00

Long/Background 253.00

Type of Entry CA Single-phase

AC input Min 90,00

AC input Max 264,00

Input frequency 50 Hz, 60 Hz

Input connector IEC 320-C14

Output voltage 57,60

Power (W) 360,00

Peak Power (W) Three hundred sixty

Output connector Screw-Type

Isolation (V) 3.000,00

Approvals CE, UL

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send MEANWELL / PB-360P-48 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.