

INDUSTRIAL COMPONENT DATA

PB-600-12 MEANWELL AC-DC Single output intelligent battery charger with 3 pin IEC-320-C14 input socket, Outp..

Brand: MEANWELL | Manufacturer Part Number: PB-600-12



Manufacturer	MEANWELL
MPN / Reference	PB-600-12
Catalog number	PB-600-12
Category	CHARGERS
Minimum order	1 unit
Document ID	EO-14887966CD
Generated	2026-08-04

Product Overview

PB-600-12 MEANWELL AC-DC Single output intelligent battery charger with 3 pin IEC-320-C14 input socket, Outp..

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **MEANWELL > CHARGERS > PB**

Additional Product Information

Name PB-600-12

Long Description Battery charger for Gel, AGM and wet. Load configurable in 2, 3 or 8 stages.

Programmable charge in 2, 3 or 8 stages.

Format metal box.

Range of universal input90-264vac. 47-63Hz.

Absorption voltageTo 14.4 Vdc.

Float voltageTo 13.8 Vdc.

Intensity of load40A.

Power:576W.

Type of batteries:Gel, AGM and wet.

Battery capacity:135-400Ah.

Efficiency typical:86%.

Factor corrector, power>0,95to 230vac at full load.

Alarm output voltage correct (DC-Ok).

Alarm for proper operation.

Compensation of the charging voltage by temperature.

Remote on / off.

3-color LED charging status indicator.

Working temperature: from -20 up to +60 °C of ambient temperature. Consult the technical data sheet to see the curves of drift.

Dimensions (Length x Width x Height) [mm]: 230 x 158 x 67.

3 years of warranty.

Manufacturer: MEAN WELL.

The series PB-600 battery chargers for lead, Gel, AGM and wet. The load type can be configured through a micro-switch to perform the load in 2, 3 or 8 stages. To compensate for the tension load according to the temperature and has a remote on / off.

Country of Origin Taiwan

Manufacturer MEAN WELL

Product type Chargers

Format Box

Subformato Grid

Applications Industrial, Solar, Telecommunications

Series PB-600

State Recommended Model

Warranty (Years) 3,00

Height (mm) 67.00

Width (mm) 158.00

Long/Background 230.00

Type of Entry CA Single-phase

AC input Min 90,00

AC input Max 264,00

Input frequency 50 Hz, 60 Hz

Input connector IEC 320-C14

Output 1 +12...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send MEANWELL / PB-600-12 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.