

INDUSTRIAL COMPONENT DATA

HRP-150-24 MEANWELL AC-DC Single output enclosed power supply, Output 24VDC / 6.5A, 1U low profile, free air..

Brand: MEANWELL | Manufacturer Part Number: HRP-150-24



Manufacturer	MEANWELL
MPN / Reference	HRP-150-24
Catalog number	HRP-150-24
Category	G6
Minimum order	1 unit
Document ID	EO-8DB4A1E4B5
Generated	2026-08-03

Product Overview

HRP-150-24 MEANWELL AC-DC Single output enclosed power supply, Output 24VDC / 6.5A, 1U low profile, free air..

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path MEANWELL > G6 > HRP

Additional Product Information

Name HRP-150-24

Long Description Switch mode power supply.

Format in case of grid.

Range of universal Input85-264vac47-63Hz.

Output voltage24vdc. Adjustable by potentiometer (21,6-28,8).

Output intensity6.5 To. Range of output current 0-6,5 according To the demand load.

Factor Corrector, Power>0,95.

Power:156W.

Function of sensing to compensate the voltage drop in the cables.

Efficiency typical:88%.

Working temperature: from-40up+70 ° Cof ambient temperature. Consult the technical data sheet to see the curves of drift.

Dimensions (Length x Width x Height) [mm]:159 x 97 x 38.

5 years of warranty.

Manufacturer: MEAN WELL.

The series HRP are the sources of most high-end format box MEAN WELL. Are designed for demanding applications.

Support input voltages of 300Vca for 5 seconds and use components of the highest reliability as the electrolytic capacitors of 105°C.

The protection against over loads is for current limiting, constant current, and can reduce stress by up to 50% of its nominal value and keeping the output intensity, this serves to start heavy loads such as motors or other inductive loads or capacitive.

Country of Origin China

Manufacturer MEAN WELL

Product type Power supply AC/DC

Format Box

Subformato Grid

Applications Industrial, Telecommunications

Series HRP-150

Warranty (Years) 5,00

Height (mm) 38.00

Width (mm) 97.00

Long/Background 159.00

Type of Entry CA Single-phase

AC input Min 85,00

AC input Max 264,00

Input frequency 50 Hz, 60 Hz

Input connector Screw-Type

O...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send MEANWELL / HRP-150-24 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.