

## INDUSTRIAL COMPONENT DATA

# LPV-35-24 MEANWELL AC-DC Single output LED driver Constant Voltage (CV), Output 24VDC / 1.5A, cable output

Brand: MEANWELL | Manufacturer Part Number: LPV-35-24



|                 |               |
|-----------------|---------------|
| Manufacturer    | MEANWELL      |
| MPN / Reference | LPV-35-24     |
| Catalog number  | LPV-35-24     |
| Category        | LED DRIVERS   |
| Minimum order   | 1 unit        |
| Document ID     | EO-236186630C |
| Generated       | 2026-07-29    |

## Product Overview

LPV-35-24 MEANWELL AC-DC Single output LED driver Constant Voltage (CV), Output 24VDC / 1.5A, cable output

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path MEANWELL > LED DRIVERS > LPV

## Additional Product Information

Name LPV-35-24

Long Description LED driver.

Specially designed to feed LED strips.

Format in box waterproof plastic IP67.

Input range 90-264vac 47-63Hz.

Output voltage 24vdc.

Output intensity 1500mA. Range of output current 0-1500mA according to demand load.

Power: 36W.

Efficiency typical: 85%.

Input class II without grounding.

Operating temperature range of case Tc from -30°C to +65°C.

Dimensions (Length x Width x Height): 148 x 40 x 30mm.

2 years of warranty.

Manufacturer: MEAN WELL.

The series LP are LED Drivers designed to work directly with LED strips. Must be equipment that is fed at constant voltage.

With plastic housing, designed for applications of LED-lighting and signalling mobile.

Have a low cost and a high reliability.

Country of Origin China

Stock Yes

Manufacturer MEAN WELL

Product type LED Driver

Format Box

Subformato IP67

Applications Industrial, Telecommunications

Series LPV-35

Warranty (Years) 3,00

Height (mm) 30.00

Width (mm) 40.00

Long/Background 148.00

Type of Entry CA Single-phase

AC input Min 90,00

AC input Max 264,00

Input frequency 50 Hz, 60 Hz

Input connector Cable

Output voltage 24,00

Power (W) 36,00

Peak Power (W) Thirty six

Output connector Cable

Isolation (V) 3.000,00

Approvals CE, UL

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send MEANWELL / LPV-35-24 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.