

INDUSTRIAL COMPONENT DATA

DBR-3200-48 MEANWELL AC-DC 19 inch rack front end charger unit with PFC, Output 55.2VDC / 55A, 1U profile, H..

Brand: MEANWELL | Manufacturer Part Number: DBR-3200-48



Manufacturer	MEANWELL
MPN / Reference	DBR-3200-48
Catalog number	DBR-3200-48
Category	CHARGERS
Minimum order	1 unit
Document ID	EO-D260330C42
Generated	2026-08-04

Product Overview

DBR-3200-48 MEANWELL AC-DC 19 inch rack front end charger unit with PFC, Output 55.2VDC / 55A, 1U profile, H..

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **MEANWELL > CHARGERS > GC**

Additional Product Information

Details

Battery charger for 19" Rack programmable via ITwoC and PMBus.

Load in 3 stages.

FormatRack 19".

Range of universal input90-264vac. 47-63Hz.

Absorption voltage57,6 Vdc.

Float voltage55,2 Vdc. Adjustable by potentiometer (47,5-58,8 cc). ProgrammableITwoC and PMBusfrom 75% to 125%.

Intensity of load55A. ProgrammableITwoC and PMBusfrom 20% to 100%.

Power:3200W.

Type of batteries:Gel, AGM, wet, Lithium-Iron and Lithium-Magnesium.

Battery capacity:180-550Ah.

Efficiency typical:94.5 per cent.

Paralelizable up to 4 units with sharing of active current and diode mosfet protection in the Rack DHP-1UT.

Hot Swapt. Change in hot.

Factor corrector, power>0,97to 230vac at full load.

Compensation of the charging voltage by temperature.

Alarm output voltage correct (DC-Ok).

Remote on / off.

Auxiliary outputs of 5V AT 0.3 A and -12V at 0.8 A. Tolerances $\pm 10\%$.

3-color LED charging status indicator.

Working temperature: from -30 up to +70 °C of ambient temperature. Consult the technical data sheet to see the curves of drift.

Dimensions (Length x Width x Height) [mm]: 325,8 x 107 x 41.

5 years of warranty.

Manufacturer: MEAN WELL.

The chargers of the series DBR-3200 are designed to install in the Rack DHP-1UT that supports up to 4 chargers DBR-3200. These chargers allow you to charge lead acid batteries, Gel, AGM, wet, Lithium-Iron and Lithium-Manganese with possibility to configure the load curves by using ITwoC and PMBus, and optionally via CANBus. By default brings of factory several load cur...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send MEANWELL / DBR-3200-48 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.