

INDUSTRIAL COMPONENT DATA

ELG-150-42DA MEANWELL AC-DC Single output LED Driver mix mode (CV+CC) with PFC, Output 42VDC / 3.57A, Dimmin..

Brand: MEANWELL | Manufacturer Part Number: ELG-150-42DA



Manufacturer	MEANWELL
MPN / Reference	ELG-150-42DA
Catalog number	ELG-150-42DA
Category	LED DRIVERS
Minimum order	1 unit
Document ID	EO-D7C158631F
Generated	2026-08-02

Product Overview

ELG-150-42DA MEANWELL AC-DC Single output LED Driver mix mode (CV+CC) with PFC, Output 42VDC / 3.57A, Dimmin..

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	MEANWELL > LED DRIVERS
--------------	------------------------

Additional Product Information

Details

LED driver dimmable.

Specially designed for powering LEDs directly in a steady stream.

Format in metal box sealed IP67.

Input range 100-305Vca 47-63Hz.

Output in constant current 3,57 A.

Range of output voltage with current mode constant 21 to 42Vcc according to demand load.

Power: 150W.

Efficiency typical: 90%.

Regulation DALI 0% to 100% of the output intensity. Certificate to DALI.

Input class I with grounding.

Factor corrector, power > 0.95 to 230vac at full load.

Consumption without load

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send MEANWELL / ELG-150-42DA with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.