

INDUSTRIAL COMPONENT DATA

HRPG-1000-24 MEANWELL AC-DC Single output Enclosed power supply with PFC, Output 24VDC / 42A, 5VDC / 0.3A au..

Brand: MEANWELL | Manufacturer Part Number: HRPG-1000-24



Manufacturer	MEANWELL
MPN / Reference	HRPG-1000-24
Catalog number	HRPG-1000-24
Category	G6
Minimum order	1 unit
Document ID	EO-77FE8E0FF6
Generated	2026-07-29

Product Overview

HRPG-1000-24 MEANWELL AC-DC Single output Enclosed power supply with PFC, Output 24VDC / 42A, 5VDC / 0.3A au..

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path MEANWELL > G6 > HRPG

Additional Product Information

Name HRPG-1000-24
 Long Description Switch mode power supply.
 Especially designed for automation applications and industrial.
 Format in case of grid.
 Range of universal input 90-264vac 47-63Hz.
 Output voltage 24vdc. Adjustable by knob (22-28Vcc).
 Output intensity 42A. Range of output current 0-42A according to demand load.
 Power: 1008W.
 Efficiency typical: 93%.
 Supports peak input voltage of 300Vca for 5 seconds.
 Factor corrector, power > 0.95 to 230vac and full load.
 Input class I with grounding.
 Alarm output voltage to the correct DC-Ok.
 Remote on / off.

Auxiliary output Stand-by 5V 0.3 A.

Consumption at no load

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send MEANWELL / HRPG-1000-24 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.