

INDUSTRIAL COMPONENT DATA

RID-125-13.5OL MEANWELL AC-DC Dual output enclosed power supply, Output $\pm 12\text{VDC}$ or $\pm 15\text{VDC}$ 118W, isolated outp..

Brand: MEANWELL | Manufacturer Part Number: RID-125-13.5OL



Manufacturer	MEANWELL
MPN / Reference	RID-125-13.5OL
Catalog number	RID-125-13.5OL
Category	G3
Minimum order	1 unit
Document ID	EO-98D756E679
Generated	2026-08-06

Product Overview

RID-125-13.5OL MEANWELL AC-DC Dual output enclosed power supply, Output $\pm 12\text{VDC}$ or $\pm 15\text{VDC}$ 118W, isolated outp..

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path MEANWELL > G3 > RID

Additional Product Information

Details

Power supply in format box with 2 isolated outputs.

Format in Case of grid

Range universal input full88-264vac47-63Hz.

Outputs:

-12vdcadjustable by potentiometer (-12 to -15vdc):

Without the need of a minimum load.

Maximum output current5,0Amps.

+12vdcadjustable by potentiometer (+12 to +15vdc):

Without the need of minimum load.

Maximum output current5,0Amps.

Power:118,8 W.

Efficiency typical:83%.

Working temperature: from-25up+70 ° C of ambient temperature. Consult the technical data sheet to see the curves of drift.

Dimensions (Length x Width x Height):199 x 98 x 38mm.

3 years of warranty.

Manufacturer: MEAN WELL.

The model RID-125-13.5 OL is a power source for industrial applications or information technology without any requirement of minimum load. It has a compact size and a high reliability by using electrolytic capacitors of 105°C. Can withstand input voltages of 300Vca for 5 seconds.

Have two isolated outputs to avoid the noise of one can affect the other.

There is a knob that lets you adjust simultaneously the 2 outputs from +/-12vdc to +/-15vdc.

Check that all the outputs do not exceed the maximum output of the power supply.

Additional information

Name RID-125-13.5 OL

Long Description Power supply in format box with 2 isolated outputs.

Format in Case of grid

Range universal input full88-264vac47-63Hz.

Outputs:

-12vdcadjustable by potentiometer (-12 to -15vdc):

Without the need of a minimum load.

Maximum output current5,0Amps.

+12vdcadjustable by potentiomete...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send MEANWELL / RID-125-13.5OL with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.