

INDUSTRIAL COMPONENT DATA

UHP-200-4.2 MEANWELL AC-DC Slim Single output enclosed power supply with PFC, Output 4.2VDC / 40A

Brand: MEANWELL | Manufacturer Part Number: UHP-200-4.2



Manufacturer	MEANWELL
MPN / Reference	UHP-200-4.2
Catalog number	UHP-200-4.2
Category	PFC
Minimum order	1 unit
Document ID	EO-A8994C9305
Generated	2026-08-05

Product Overview

UHP-200-4.2 MEANWELL AC-DC Slim Single output enclosed power supply with PFC, Output 4.2VDC / 40A

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	MEANWELL > PFC
--------------	----------------

Additional Product Information

Details

Switched Power supply in case of grid.

Certified source for industrial applications, and home automation.

Format in case of grid. U-type with low profile.

Range of universal input 90-264vac 47-63Hz.

Output voltage 4,2 Vdc. Adjustable by potentiometer (3,6-4,4 Vcc).

Output intensity 40A. Range of output current 0-40A according to demand load.

Power: 168W.

Efficiency typical: 90%.

Factor corrector, power > 0,94 to 230vac at full load.

Protection against short circuit, over load, over voltage and temperature.

Input class I with grounding.

LED indicator of operation.

Operating altitude up to 5000 metres.

Working temperature: from -30°C up to +70 ° C of ambient temperature. Consult the technical data sheet to see the curves of

drift.

Dimensions (Length x Width x Height) [mm]:194 x 55 x 26.

3 years warranty.

Manufacturer: MEAN WELL

The series UHP are switching power supplies grid-type, U-shape and low profile with high efficiency. Support input voltages of 300Vca for 5 seconds and use components of the highest reliability. Support peak loads of up to 150%, during 100ms, which allows you to start heavy loads or withstand spikes without the need to oversize the power source. Have a power LED. Are certified to operate up to 5000 meters of altitude. Have multiple protections (short circuit, overload, over voltage and temperature). Designed for multiple applications such as mechanical and electrical equipment, appliances, LED panels, industrial machinery, control of industrial systems. Are cert...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send MEANWELL / UHP-200-4.2 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.