

INDUSTRIAL COMPONENT DATA

AK1/AP-4AAN MICRO DETECTORS Inductive sensor M18 unshielded NO/PNP cable 2m axial II 3G Ex nA IIC T5, II 3D ..

Brand: MICRO DETECTORS | Manufacturer Part Number: AK1/AP-4AAN



Manufacturer	MICRO DETECTORS
MPN / Reference	AK1/AP-4AAN
Catalog number	AK1/AP-4AAN
Category	Encoders
Minimum order	1 unit
Document ID	EO-88720BAF3D
Generated	2026-08-03

Product Overview

AK1/AP-4AAN MICRO DETECTORS Inductive sensor M18 unshielded NO/PNP cable 2m axial II 3G Ex nA IIC T5, II 3D ..

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	MICRO DETECTORS > Encoders
--------------	----------------------------

Additional Product Information

Technical features

Detection properties

Nominal sensing distance 0,6mm

Operanting distance 0...0,48mm

Standard target 4x4mm FE360

Correction Factor copper: $0,32 \pm 10\%$ / aluminium: $0,24 \pm 10\%$ / brass: $0,39 \pm 10\%$ / stainless steel: $0,57 \pm 10\%$

Thermal drift of Sr < 10%

Repeat Accuracy 5% (UB 24V Ta=23°C $\pm 5^{\circ}\text{C}$)

Hysteresis 1 ... 20%

Outputs

Output type NPN

Output Function NO

Switching frequency 3kHz

Electrical data

Operating Voltage 10 - 30Vdc

No-Load supply current $\leq 10\text{mA}$
Load current $\leq 100\text{mA}$
Leakage current $\leq 10\mu\text{A}$
Output voltage drop $\leq 1,5\text{V}$ @100mA
Max ripple content $\leq 10\%$
LED indicators Yellow LED output state
Time delay before availability $\leq 50\text{ms}$
Short-circuit protection Yes (auto-reset)
Reverse Polarity Protection Yes
Protection against inductive loads Yes
Mechanical data
Dimensions $\varnothing 3 / L = 22\text{mm}$
Mounting Shielded
Weight 30g
Housing Material AISI303 Stainless Steel
Connections 2m PUR Cable
Active Head Material PBT
Operating temperature $-25^{\circ}\text{C} \dots +70^{\circ}\text{C}$
Test/Approvals
Approvals CEUL
EMC compatibility IEC 60947-5-2
Shocks and vibrations Vibration IEC 60068-2-6 / Shock IEC 60068-2-27
Degree of protection IP 67 (EN60529)
Electrical diagrams of the connections
Dimension (mm)
Installation
Response curves
Disassamento Parallelo

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send MICRO DETECTORS / AK1/AP-4AAN with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.