

INDUSTRIAL COMPONENT DATA

2CDG110110R0011 MT/S 8.12.2M NIESSEN MT/S8.12.2M Security Terminal, 8-fold

Brand: NIESSEN | Manufacturer Part Number: 2CDG110110R0011

PRODUCT IMAGE\nNOT
AVAILABLE

Manufacturer	NIESSEN
MPN / Reference	2CDG110110R0011
Catalog number	MT/S 8.12.2M
Category	Sensor control for bus system
Minimum order	1 Pcs
Document ID	EO-8A28186AA3
Generated	2026-07-31

Product Overview

TERMINAL DE ZONA, 8 CANALES

ZONE TERMINAL, 8 CHANNELS

used for the monitored connection of sensors from security technology (e.g. magnetic contacts or glass-breakage sensors) to the ABB i-bus® KNX. The device has eight inputs ("zones") available and can be used as a stand-alone security system or in combination with the security module or intrusion alarm panel with KNX interface. 12 V DC SELV power supply required, e.g. NTU/S 12.2000.1. Typical applications are door and window surveillance, glas-breakage detection as well as area surveillance.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **NIESSEN > KNX-EIB**

Additional Product Information

Extended Product Type:MT/S8.12.2M

Product ID:2CDG110110R0011

EAN:4016779711869

Catalog Description:MT/S8.12.2M Security Terminal, 8-fold, MDRC

Long Description:used for the monitored connection of sensors from security technology (e.g. magnetic contacts or glass-breakage sensors) to the ABB i-bus® KNX. The device has eight inputs ("zones") available and can be used as a stand-alone security system or in combination with the security module or intrusion alarm panel with KNX interface. 12 V DC SELV power supply required, e.g. NTU/S 12.2000.1. Typical applications are door and window surveillance, glas-breakage detection as well as area surveillance.

Installation

Instructions and Manuals:2CDG941072P0002

Technical

Data Sheet, Technical Information:2CDC513044D0201

2CDC513045D0201

Auxiliary Voltage AC/DC:12 V DC

Output Voltage (U_{out}):12 V DC

Maximum Switching Current:0.6 A

Power Loss:1.2 W

Number of Outputs:3

Number of Input Channels:8

Compatible Bus Systems:KNX (TP)

Product Range:KNX

Mounting Type:DIN-Rail

Sensor Type:Signalling group terminal

Manual Operation:Yes

Color:light grey

Number of Batteries:0

Application Function:Safety and Security

Environmental

Degree of Protection:IP20

RoHS Status:Following EU Directive 2011/65/EU

RoHS Information:2CDK513014D2701

REACH Declaration:9AKK108468A9644

Conflict Minerals Reporting Template (CMRT):9AKK108468A3363

Dimensions

Width in Number of Modular Spacings:4

Product Net Width:72mm

Product Net Height:90mm

Product Net Depth / Length:64.5mm....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send NIESSEN / 2CDG110110R0011 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.