

INDUSTRIAL COMPONENT DATA

2CLA225180N1801 N2251.8 AN NIESSEN N2251.8 AN TV R/SAT outlet loop through 2M

Brand: NIESSEN | Manufacturer Part Number: 2CLA225180N1801



Manufacturer	NIESSEN
MPN / Reference	2CLA225180N1801
Catalog number	N2251.8 AN
Category	Insert/cover for communication technology
Minimum order	10 Pcs
Document ID	EO-272894E4A5
Generated	2026-08-03

Product Overview

Toma TV-R/SAT intermedia AN

Intermediate TV-R/SAT AN socket

Color: Anthracite. TV-R and SAT double outlet - Intermediate. Installation as an intermediate outlet in series connected to each other. Output connectors (C1 / C2): IEC male 9,52 mm. diam. / IEC female 9,52 mm. diam. Frequency range (I/O / C1 / C2): 5 - 2.400 MHz / 5 - 2.400 MHz / 5 - 2.400 MHz. Basic loss (FM / TV / SAT): 10,0±1,0 dB / 10,0±1,0 dB / 12,0±2,0 dB. Through loss (FM / TV / SAT): 2,5±0,5 / 2,5±0,7 / 3,0±1,0. Directivity (FM / TV / SAT): >20 / >12 / >5. Isolation (FM / TV / SAT): >45 / >30 / >28. Return loss (VR / FM / TV / SAT): >13 / >13 / >12 / >12. DC path (Vdc / mA / Tono): 24 max. / 500 max. / 22 KHz - DiSEqC. Size: 2 modules.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path NIESSEN > Flush-mounting series > Zenit Noble

Additional Product Information

Extended Product Type: N2251.8 AN

Product ID: 2CLA225180N1801

EAN: 8427238060507

Catalog Description: TV outlet SAT 2 gang Anthracite - Zenit

Long Description: Color: Anthracite.

TV-R and SAT double outlet - Intermediate.

Installation as an intermediate outlet in series connected to each other.

Output connectors (C1 / C2):

IEC male 9,52 mm. diam. / IEC female 9,52 mm. diam.

Frequency range (I/O / C1 / C2):

5 - 2.400 MHz / 5 - 2.400 MHz / 5 - 2.400 MHz.

Basic loss (FM / TV / SAT):

10,0±1,0 dB / 10,0±1,0 dB / 12,0±2,0 dB.

Through loss (FM / TV / SAT):

2,5±0,5 / 2,5±0,7 / 3,0±1,0.

Directivity (FM / TV / SAT): >20 / >12 / >5.

Isolation (FM / TV / SAT): >45 / >30 / >28.

Return loss (VR / FM / TV / SAT): >13 / >13 / >12 / >12.

DC path (Vdc / mA / Tono):

24 max. / 500 max. / 22 KHz - DiSEqC.

Size: 2 modules.

Installation

Instructions and Manuals:2CLX210109N1001

Technical

Data Sheet, Technical Information:9AKK10103A5108

Application:SAT

Design Range:Zenit

Mounting Type:Flush Mounted

Type of Fastening:Engage (Snap)

Type of Indicator:Without indication field

Outlet Orientation:Straight

Surface Finishing:Decor

Matt

Material:Plastic

Thermoplastic

Color:Anthracite

Number of Batteries:0

Environmental

Ambient Air Temperature:Operation -5 ... +35 °C

Storage -5 ... +50 °C

Degree of Protection:IP20

RoHS Status:Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

RoHS Information:2CLC225180N1801

REACH Declaration:9AKK108467A7464

Conflict Minerals Reporting Template (CMRT):9AKK10846...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send NIESSEN / 2CLA225180N1801 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.