

INDUSTRIAL COMPONENT DATA

1111640 OBO BETTERMANN PROFILE C2518

Brand: OBO BETTERMANN | Manufacturer Part Number: C2518



Manufacturer	OBO BETTERMANN
MPN / Reference	C2518
Catalog number	1111640
Category	Mounting rail/-profile
Minimum order	2 m.
Document ID	EO-345A5614D6
Generated	2026-07-29

Product Overview

PROFILE C2518

CL2518 profile rail, slot 17 mm, FS, perforated. Central C profile rail for cable routing, in conjunction with clamp clips with a hammerhead foot. Can also be used as suspension construction for cable support systems.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	OBO BETTERMANN > VBS Connection and fastening systems - OBO BETTERMANN
--------------	--

Additional Product Information

CO2 Footprint (GWP) Cradle-to-Gate 1,3803 kg CO2e / 1 Meter

Dimension 2000x25x18

Dimension L 2000 mm

Height 18 mm

Hole shape (ETIM) Long slot

Length 2000 mm

Maintain electrical functions no

Material Steel

Material thickness 1,25 mm

Profile shape C profile

Slot width 17 mm

Static value A 0,67 cm²Static value Iy 0,26 cm⁴Static value Iz 0,78 cm⁴

Static value Wy 0,21 cm³

Static value Wz 0,75 cm³

Surface Strip galvanized

Type of perforation Perforated back

Version for Single profile

Width 25 mm

With perforation yes

With tothing no

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / C2518 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.