

INDUSTRIAL COMPONENT DATA

1268 L 800 FS 1104320 OBO BETTERMANN PROFILE, PERFORATED, SLOT 17MM CML3518P0800FS

Brand: OBO BETTERMANN | Manufacturer Part Number: 1268 L 800 FS



Manufacturer	OBO BETTERMANN
MPN / Reference	1268 L 800 FS
Catalog number	1104320
Category	Extruded profile modular housing
Minimum order	10 Pcs
Document ID	EO-F9E80724AC
Generated	2026-08-03

Product Overview

PROFILE, PERFORATED, SLOT 17MM CML3518P0800FS

CML3518 profile rail, slot 17 mm, FS, perforated. Light-duty profile rail, perforated, slot width 17 mm.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path OBO BETTERMANN > VBS Connection and fastening systems - OBO BETTERMANN

Additional Product Information

Breakable no
CO2 Footprint (GWP) Cradle-to-Gate 1,4251 kg CO2e / 1 Piece
Dimension 800x35x18
Dimension L 800 mm
Drill hole spacing, centre 25 mm
Height 18 mm
Length 800 mm
Maintain electrical functions yes
Material Steel
Material thickness 1,25 mm
Profile shape C profile
Rustproof steel, pickled no
Slot width 17 mm
Static value A 0,88 cm²

Static value I_y 0,41 cm⁴
Static value I_z 1,81 cm⁴
Static value W_y 0,41 cm³
Static value W_z 1,03 cm³
Surface Strip galvanized
Type of perforation Perforated back
Version for Single profile
Width 35 mm
With perforation yes
With tothing no

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / 1268 L 800 FS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.