

INDUSTRIAL COMPONENT DATA

1814 ST D37 5014477 OBO BETTERMANN Connection terminal for large reinforced steels

Brand: OBO BETTERMANN | Manufacturer Part Number: 1814 ST D37



Manufacturer	OBO BETTERMANN
MPN / Reference	1814 ST D37
Catalog number	5014477
Category	Connector for lightning protection
Minimum order	25 Pcs
Document ID	EO-8E315BE19C
Generated	2026-08-03

Product Overview

Connection terminal for large reinforced steels

VARIO Hug/lay/ground/press 1814 ST D37, for armor 16-37mm 61x46x88 Steel, St,

VARIO earthing terminal for large reinforced steels. • For armoured steel with 16-37 mm diameter and round conductors and flat conductors• Rapid installation using open slot and only one M10 bolt• Rotatable metal pressure trough for simple, safe mounting

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path OBO BETTERMANN > TBS Transient and lightning protection systems - OBO BETTERMANN

Additional Product Information

CO2 Footprint (GWP) Cradle-to-Gate 1,0445 kg CO2e / 1 Piece

Dimension 61x46x88

Earthing connection diameter 20-30 mm

Fit FL30x3-4mm / Rd 10 x Rd 16-37 mm

Lightning current carrying capacity H/100 kA

Material Steel

Suitable for connection Miscellaneous

Type of connector Multipurpose connection clamp

Type of fastening screw Hexagonal bolt

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / 1814 ST D37 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.