

**INDUSTRIAL COMPONENT DATA**

# 2024919 OBO BETTERMANN PRENS. DIVISIBLE V-TEC TB25 11-15

Brand: OBO BETTERMANN | Manufacturer Part Number: V-TEC TB25 12-15



|                 |                  |
|-----------------|------------------|
| Manufacturer    | OBO BETTERMANN   |
| MPN / Reference | V-TEC TB25 12-15 |
| Catalog number  | 2024919          |
| Category        | Cable gland      |
| Minimum order   | 5 Pcs            |
| Document ID     | EO-035694EC53    |
| Generated       | 2026-07-31       |

## Product Overview

### PRENS. DIVISIBLE V-TEC TB25 11-15

Divisible cable gland, seal insert, 1 cable, light grey. The splittable cable gland V-TEC TB.. ensures - like all V-TEC glands - a secure sealing of the cable. The installation of pre-terminated cables or function cables, for example, is easy and quick, thanks to the splitting of the cable gland. The V-TEC TB is also unbeatable when refitting an existing installation and as a "repair gland". There is no need to disassemble pre-mounted cables, it can be installed without interrupting the production process. The gland set consists of an intermediate support, a cap nut and the seal. Of course, the split locknut is also in the scope of delivery.

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path **OBO BETTERMANN > VBS Connection and fastening systems - OBO BETTERMANN**

## Additional Product Information

Bend protection no  
CO2 Footprint (GWP) Cradle-to-Gate 0,12 kg CO2e / 1 Piece  
Colour Light grey  
Dimension M25  
Dimension D 15 mm  
Dimension E1 (mm) 38,5 mm  
Dimension E2 33,8 mm  
Dimension G M25x1,5 mm  
Dimension L 41 mm

Dimension L max. 40 mm  
Dimension L min. 31,5 mm  
Dimension L1 11 mm  
Dimension L2 10 mm  
Dimension L3 9 mm  
explosion-proof no  
Fibre-glass reinforced no  
Flame-resistant acc. to VDE 0471/DIN 695 Part 2-1, test temperature 650°C  
Flat cable gland no  
For Ex zone Without  
For Ex zone dust Without  
For Ex zone gas Without  
Halogen-free yes  
Height 50 mm  
Impact-resistant yes  
Length 35 mm  
Material Polycarbonate  
Nominal thread size 25  
Number of drill holes 1  
Permitted temperature range, max. 80 °C  
Permitted temperature range, min. -20 °C  
Protection rating IP67  
Sealing area D, max. 15 mm  
Sealing area D, min. 12 mm  
Sealing insert, multiple no  
Splittable gland yes  
Strain relief option no  
Thread M25 x 1,5  
Thread increase 1,5 mm  
Thread length 11 mm  
Thread type Metric  
Type of seal Sealing ring  
Unstable torque 4 Nm  
Version for Straight  
WAF 1 35 mm  
WAF 2 31 mm  
Width 38,5 mm  
With locknut yes

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / V-TEC TB25 12-15 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.