

INDUSTRIAL COMPONENT DATA

2024925 OBO BETTERMANN PRENS. DIVISIBLE V-TEC TB25 17-20

Brand: OBO BETTERMANN | Manufacturer Part Number: V-TEC TB25 18-20



Manufacturer	OBO BETTERMANN
MPN / Reference	V-TEC TB25 18-20
Catalog number	2024925
Category	Cable gland
Minimum order	5 Pcs
Document ID	EO-EB56045A38
Generated	2026-07-28

Product Overview

PRENS. DIVISIBLE V-TEC TB25 17-20

Divisible cable gland, seal insert, 1 cable, light grey. The splittable cable gland V-TEC TB.. ensures - like all V-TEC glands - a secure sealing of the cable. The installation of pre-terminated cables or function cables, for example, is easy and quick, thanks to the splitting of the cable gland. The V-TEC TB is also unbeatable when refitting an existing installation and as a "repair gland". There is no need to disassemble pre-mounted cables, it can be installed without interrupting the production process. The gland set consists of an intermediate support, a cap nut and the seal. Of course, the split locknut is also in the scope of delivery.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path

OBO BETTERMANN > VBS Connection and fastening systems - OBO BETTERMANN

Additional Product Information

Bend protection no

CO2 Footprint (GWP) Cradle-to-Gate 0,1058 kg CO2e / 1 Piece

Colour Light grey

Dimension M25

Dimension D 20 mm

Dimension E1 (mm) 38,5 mm

Dimension E2 33,8 mm

Dimension G M25x1,5 mm

Dimension L 41 mm

Dimension L max. 40 mm
Dimension L min. 31,5 mm
Dimension L1 11 mm
Dimension L2 10 mm
Dimension L3 9 mm
explosion-proof no
Fibre-glass reinforced no
Flame-resistant acc. to VDE 0471/DIN 695 Part 2-1, test temperature 650°C
Flat cable gland no
For Ex zone Without
For Ex zone dust Without
For Ex zone gas Without
Halogen-free yes
Height 50 mm
Impact-resistant yes
Length 35 mm
Material Polycarbonate
Nominal thread size 25
Number of drill holes 1
Permitted temperature range, max. 80 °C
Permitted temperature range, min. -20 °C
Protection rating IP67
Sealing area D, max. 20 mm
Sealing area D, min. 18 mm
Sealing insert, multiple no
Splittable gland yes
Strain relief option no
Thread M25 x 1,5
Thread increase 1,5 mm
Thread length 11 mm
Thread type Metric
Type of seal Sealing ring
Unstable torque 4 Nm
Version for Straight
WAF 1 35 mm
WAF 2 31 mm
Width 38,5 mm
With locknut yes

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / V-TEC TB25 18-20 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.