

INDUSTRIAL COMPONENT DATA

2054450 OBO BETTERMANN TERMINAL S/SCREWS 61 225 FL

Brand: OBO BETTERMANN | Manufacturer Part Number: 61 225 FL



Manufacturer	OBO BETTERMANN
MPN / Reference	61 225 FL
Catalog number	2054450
Category	Push in terminal
Minimum order	100 Pcs
Document ID	EO-C9A283ED98
Generated	2026-07-29

Product Overview

TERMINAL S/SCREWS 61 225 FL

Universal plug-in terminal, 2-pole. Tested according to EN 60998. Screwless terminal to connect electrical conductors. The type of conductor can either be flexible, multi-wire or rigid. If rigid conductors are used, an opening of the release lever is not necessary. The conductor can be plugged into the terminal directly. To extract the conductors, simply open the release lever. The strand can then be easily pulled-out. Nominal cross-section: 2 x 0.2 - 2.5 mm² multi-wire cables / single-wire conductors. Rated voltage 450 V. Rated current 24 A. Stripping length: 9 mm (+1 mm). Inspection opening: Phase tester and testing pin (max. Ø 2 mm), very easily accessible on the top side of the terminal. Max. approved ambient temperature according to EN 60998: -5 to +85 °C.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path OBO BETTERMANN > VBS Connection and fastening systems - OBO BETTERMANN

Additional Product Information

Colour Transparent

Connectable conductor cross-section, multi-wire, max. 2,5 mm²

Connectable conductor cross-section, multi-wire, min. 0,2 mm²

Connectable conductor cross-section, single-wire, max. 2,5 mm²

Connectable conductor cross-section, single-wire, min. 0,2 mm²

Cross-section 2 x 0.2 - 2.5 mm² multi-wire cables / single-wire conductors mm²

Dimension 0,2-2,5mm²

Flame-resistant Acc. to VDE 0471/DIN 695 Part 2-1, test temperature 850°C

Height 11,7 mm

Insulation material Thermoplast
Length 11,9 mm
Material Polycarbonate
No. of terminals 2
Nominal cross-section, max. 2,5 mm²
Nominal cross-section, min. 0,2 mm²
Nominal current 24 A
Nominal voltage 450 V
Permitted temperature range, max. 85 °C
Permitted temperature range, min. -5 °C
Pole number 1
Suitable for flexible conductors yes
Suitable for multi-wire conductors yes
Suitable for solid conductors yes
Width 21 mm
With actuating levers yes

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / 61 225 FL with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.