

INDUSTRIAL COMPONENT DATA

2331800 OBO BETTERMANN FLANGE 565 2.5x75 BL PA

Brand: OBO BETTERMANN | Manufacturer Part Number: 565 2.5x75 WS



Manufacturer	OBO BETTERMANN
MPN / Reference	565 2.5x75 WS
Catalog number	2331800
Category	Cable tie
Minimum order	100 Pcs
Document ID	EO-55BE64905A
Generated	2026-07-31

Product Overview

FLANGE 565 2.5x75 BL PA

Cable tie, white. Cable ties are used for quick, uncomplicated fixing or bundling of cables and pipes to cable support systems or other mounting structures.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path OBO BETTERMANN > VBS Connection and fastening systems - OBO BETTERMANN

Additional Product Information

CO2 Footprint (GWP) Cradle-to-Gate 0,0008 kg CO2e / 1 Piece

Colour White

Dimension 2,4x75mm

Dimension B 2,5 mm

Dimension L 75 mm

Dimension t 1 mm

Fastening type Without

Halogen-free yes

Height 1 mm

Labelling area Without

Length 75 mm

Material Polyamide

Max. Bundle diameter 15 mm

MIL approval no

Min. mounting temperature -30 °C
Mounting temperature, max. 90 °C
Permitted temperature range, max. 90 °C
Permitted temperature range, min. -30 °C
Reflective no
Releasable lock no
Strip closure Plastic tongue/tab
Tensile strength 80 N
Transparent no
UL approval yes
UV-resistant no
Version for Externally toothed
VG approval no
Width 2,5 mm

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / 565 2.5x75 WS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.