

INDUSTRIAL COMPONENT DATA

565 4.8x200 SWUV 2331874 OBO BETTERMANN FLANGE 565 4.8x200 NG UV PA

Brand: OBO BETTERMANN | Manufacturer Part Number: 565 4.8x200 SWUV



Manufacturer	OBO BETTERMANN
MPN / Reference	565 4.8x200 SWUV
Catalog number	2331874
Category	Cable tie
Minimum order	100 Pcs
Document ID	EO-581EA26F24
Generated	2026-08-03

Product Overview

FLANGE 565 4.8x200 NG UV PA

Cable tie 565 4.8x200 SWUV, UV resistant 4.8x200mm Polyamide, PA,

Cable tie, black, UV and weather-resistant. Cable ties are used for quick, uncomplicated fixing or bundling of cables and pipes to cable support systems or other mounting structures.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	OBO BETTERMANN > VBS Connection and fastening systems - OBO BETTERMANN
--------------	--

Additional Product Information

CO2 Footprint (GWP) Cradle-to-Gate 0,006 kg CO2e / 1 Piece

Colour Black

Dimension 4,8x200mm

Dimension B 4,8 mm

Dimension L 200 mm

Dimension t 1,6 mm

Fastening type Without

Halogen-free yes

Height 1,6 mm

Labelling area Without

Length 200 mm

Material Polyamide

Max. Bundle diameter 52 mm
MIL approval no
Min. mounting temperature -30 °C
Mounting temperature, max. 90 °C
Permitted temperature range, max. 90 °C
Permitted temperature range, min. -30 °C
Reflective no
Releasable lock no
Strip closure Plastic tongue/tab
Tensile strength 220 N
Transparent no
UL approval yes
UV-resistant yes
Version for Externally toothed
VG approval no
Width 4,8 mm
ETIM for 2331874 Fixings and fasteners (EC000046)
Feature Name
Feature Value
Band width (EF008160)
4.8 mm
Length belt/tape/tie (EF000063)
200 mm
Tie thickness (EF004499)
1.6 mm
Bundle diameter (EF007719)
52 mm
Operating temperature (EF002393)
-30 °C
Mounting temperature (EF008326)
-30 °C
Model (EF000010)
External toothing
Band closure (EF007673)
Plastic lip/-cam
Material (EF002169)
Plastic
Material quality (EF001257)
Polyamide (PA)
Halogen free (EF000025)
Yes
Colour (EF000007)
Black
Transparent (EF006243)
No
Fluorescent (EF009518)
No

Text strip (EF000129)

None

Releasable closure (EF004907)

No

Type of fastening (EF002442)

None

VG approval (EF008107)

No

MIL approval (EF007933)

No

UL approval (EF008093)

Yes

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / 565 4.8x200 SWUV with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.