

INDUSTRIAL COMPONENT DATA

5000025 OBO BETTERMANN PICA EARTH 219/25 FT 1.5 M

Brand: OBO BETTERMANN | Manufacturer Part Number: 219 25 OMEX FT



Manufacturer	OBO BETTERMANN
MPN / Reference	219 25 OMEX FT
Catalog number	5000025
Category	Earth rod/profiled earth rod
Minimum order	5 Pcs
Document ID	EO-63EB51CB5E
Generated	2026-08-01

Product Overview

PICA EARTH 219/25 FT 1.5 M

Earth rod OMEX, hot galvanised, 25 mm. • OMEX system• With peg and bore for linking together• With hardened hexagonal pins• Min. zinc coating 60 µm• Very good contacting properties with soft metal inlay in the bore hole• Conforms to the requirements according to VDE 0185-305 (IEC 62305) and DIN EN 62561-2

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	OBO BETTERMANN > TBS Transient and lightning protection systems - OBO BETTERMANN
--------------	--

Additional Product Information

CO2 Footprint (GWP) Cradle-to-Gate 15,9491 kg CO2e / 1 Piece

Dimension 1,5m

Dimension D 25 mm

External diameter 25 mm

Length 1500 mm

Lightning current carrying capacity H/100 kA

Material Steel

Profile type Round D=25 mm

Short-circuit current (50 HZ)(1 s;<=300°C) 12,3 kA

Surface Hot-dip galvanised

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / 219 25 OMEX FT with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.