

INDUSTRIAL COMPONENT DATA**5093518 OBO BETTERMANN ARRESTER 1+2 V50-4+FS-280**

Brand: OBO BETTERMANN | Manufacturer Part Number: V50-4+FS-280



Manufacturer	OBO BETTERMANN
MPN / Reference	V50-4+FS-280
Catalog number	5093518
Category	Combined arrester for power supply systems
Minimum order	1 Pcs
Document ID	EO-5C0583794F
Generated	2026-07-31

Product Overview

ARRESTER 1+2 V50-4+FS-280

STRUCTURED PRODUCT DATA**Technical Specifications**

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog PathCatalog path **OBO BETTERMANN > TBS Transient and lightning protection systems - OBO BETTERMANN****Additional Product Information**

Lightning current combination arrester, type 2

- For the equipotential bonding of lightning current to VDE 0185-305 (IEC 62305)
- Lightning current discharge capacity of 12.5 kA (10/350) per pole and up to 50 kA (10/350) in total
- Modular, plug-in arrester with dynamic cut-off unit and visual status display
- Locking mechanism with vibration protection and voltage keying
- Halogen-free plastic (UL 94 V-0)
- The remote signalling (FS) variants have a potential-free changeover contact for remote signalling

Application: Lightning current equipotential bonding for buildings of class III and IV.

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / V50-4+FS-280 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.