

INDUSTRIAL COMPONENT DATA

V20-0-320 5095366 OBO BETTERMANN DOWNLOADER T. 2

V20-0-320

Brand: OBO BETTERMANN | Manufacturer Part Number: V20-0-320



Manufacturer	OBO BETTERMANN
MPN / Reference	V20-0-320
Catalog number	5095366
Category	Surge protection device for power supply systems
Minimum order	1 Pcs
Document ID	EO-818832336E
Generated	2026-08-03

Product Overview

DOWNLOADER T. 2 V20-0-320

Surge arrester V20 active part 320V

Plug-in arrester V20 320 V. Surge arrester, type 2 • For surge protection equipotential bonding to VDE 0100-443 (IEC 60364-4-44) • Discharge capacity to 40 kA (8/20) per pole through high-performance varistors • Modular, plug-in arrester with dynamic cut-off unit and visual status display • Locking mechanism with vibration protection and voltage keying • Plastic (UL 94 V-0)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **OBO BETTERMANN > TBS Transient and lightning protection systems - OBO BETTERMANN**

Additional Product Information

Approvals VDE, KEMA, UL, ÖVE

Blow-out no

CO2 Footprint (GWP) Cradle-to-Gate 0,2508 kg CO2e / 1 Piece

Dimension 320V

Housing material surge protection components PA UL 94 V-0

Installation type On basic element

Integrated back-up fuse no

Maximum continuous voltage (L-N) 320 V

Maximum continuous voltage AC 320 V

Maximum discharge current (8/20 us) 40 kA

Maximum discharge current (8/20 us) [L-N] 40 kA
Minimum distance 1,5 mm
Network form Other
Nominal discharge current (8/20 μs) 20 kA
Nominal discharge current (8/20 μs) [L-N] 20 kA
Nominal voltage AC (50/60 Hz) 230 V
Operating temperature, max. 80 °C
Operating temperature, min. -40 °C
Permitted temperature range, max. 80 °C
Permitted temperature range, min. -40 °C
Pole number 1
Pole version 1
Protection level [L-N] ≤1,4
Protection rating IP20
Remote signalling no
Residual voltage [L-N] @ 1 kA 1 kV
Residual voltage [L-N] @ 5 kA 1,2 kV
Short-circuit resistance for max. mains-side overcurrent protection 50 kA eff
Short-circuit resistant yes
Signalling on device Visual
SPD to EN 61643-11 Type 2
SPD to IEC 61643-1 Class II
SPD to UL 1449 Type 4
Test class, type 2 yes

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / V20-0-320 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.