

INDUSTRIAL COMPONENT DATA

5098412 OBO BETTERMANN DOWNLOADER-EX MDP-4 D-5-EX

Brand: OBO BETTERMANN | Manufacturer Part Number: MDP-4 D-5-EX



Manufacturer	OBO BETTERMANN
MPN / Reference	MDP-4 D-5-EX
Catalog number	5098412
Category	Surge protection device for data networks/MCR-technology
Minimum order	1 Pcs
Document ID	EO-9A4C2A6DB7
Generated	2026-08-02

Product Overview

DOWNLOADER-EX MDP-4 D-5-EX

Series protection device, 4-pole, 5 V version. Lightning barrier for intrinsically safe measuring circuits • Protection device for multi-wire systems • Direct shield earthing and screwless connection terminals • Space-saving width of just 8.7 mm • High frequency range of 0-100 MHz • ATEX approval: II 2(1) G Ex ia [ia Ga] IIC T4 (BVS 11 ATEX E 131 X) • UL-listed (4UM2) Application: Universal use on 35 mm DIN profile rail in any standard distribution housing.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path OBO BETTERMANN > TBS Transient and lightning protection systems - OBO BETTERMANN

Additional Product Information

Approvals UL

Arrestor monitoring no

Capacity (wire-wire) < 40 pF

CO2 Footprint (GWP) Cradle-to-Gate 0,1887 kg CO2e / 1 Piece

Colour Blue

Connection cross-section, flexible, max. 2,5 mm²

Connection cross-section, flexible, min. 0,14 mm²

Connection cross-section, multi-wire, max. 1,5 mm²

Connection cross-section, multi-wire, min. 0,14 mm²

Connection cross-section, rigid, max. 2,5 mm²

Connection cross-section, rigid, min. 0,14 mm²

Cut-off frequency 100 MHz
Dimension 5V
Earthing via: DIN rail
EX approval II 2(1)G Ex ia [ia Ga] IIC T4 Gb
Impulse durability wire-earth C2: 5 KV / 2,5 kA (8/20µs)
Impulse durability wire-wire C1: 0,5 KV / 0,25 kA (8/20µs)
Insertion loss <=3 dB
Insulation resistance >100 M?
Kategorie Type 1+2+3 / D1+C2+C1
Lightning protection zone LPZ 0->3
Maximum continuous voltage AC 7 V
Maximum continuous voltage DC 10 V
Nominal load current AC 0,4 A
Nominal load current DC 0,58 A
Nominal voltage 5 V
Number of poles 4
Permitted temperature range, max. 80 °C
Permitted temperature range, min. -40 °C
Plug-in system Terminal
Protection level wire-earth

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / MDP-4 D-5-EX with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.