

INDUSTRIAL COMPONENT DATA

5408024 OBO BETTERMANN ELEMENT CONNECTION isCONIN

Brand: OBO BETTERMANN | Manufacturer Part Number: isCon IN connect



Manufacturer	OBO BETTERMANN
MPN / Reference	isCon IN connect
Catalog number	5408024
Category	Air-termination equipment for lightning protection
Minimum order	1 Pcs
Document ID	EO-72F01992F6
Generated	2026-07-29

Product Overview

ELEMENT CONNECTION isCONIN

Connection element for installation in the insulated interception rod isFang IN. • Screw-on termination of the connection for the isCon® cable • Connection and installation of the cable in the insulated interception rod • Tested up to 150 kA (lightning protection Class II)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path OBO BETTERMANN > TBS Transient and lightning protection systems - OBO BETTERMANN

Additional Product Information

Clamping range, max. 23 mm
CO2 Footprint (GWP) Cradle-to-Gate 1,2871 kg CO2e / 1 Piece
Dimension Ø23mm
Dimension d min. 28 mm
Fit 23 mm
Lightning current carrying capacity H1/150 kA
Material Stainless steel 1.4301
Suitable for connection Miscellaneous

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / isCon IN connect with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.