


**INDUSTRIAL COMPONENT DATA**

# 6059515 OBO BETTERMANN TRAY SKSMAGIC 640 VA4571

Brand: OBO BETTERMANN | Manufacturer Part Number: SKSM 640 VA4571



|                 |                                 |
|-----------------|---------------------------------|
| Manufacturer    | OBO BETTERMANN                  |
| MPN / Reference | SKSM 640 VA4571                 |
| Catalog number  | 6059515                         |
| Category        | Cable tray/wide span cable tray |
| Minimum order   | 3 Pcs                           |
| Document ID     | EO-3E0C8D8B78                   |
| Generated       | 2026-08-02                      |

## Product Overview

TRAY SKSMAGIC 640 VA4571

Cable tray SKS-Magic® 60 A4. Cable tray with integrated quick fastening system. The usable length of the cable tray is 3,000 mm. The cable tray has continuous side perforations of 7 x 20 mm for the installation of additional connection and mounting components. From a cable tray width of 200 mm with 30% hole surface, suitable for use under sprinkler systems according to VdS guideline 2092.

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                                             |
|--------------|-------------------------------------------------------------|
| Catalog path | OBO BETTERMANN > KTS cable support systems - OBO BETTERMANN |
|--------------|-------------------------------------------------------------|

## Additional Product Information

CO2 Footprint (GWP) Cradle-to-Gate 31,2825 kg CO2e / 1 Meter

Colour stainless steel

Connector version Integrated connector

Dimension 60x400x3050

Dimension B 400 mm

Dimension L 280 mm

Dimension x 296 mm

Dimension y 362 mm

Height 60 mm

Length 3050 mm

Load test type according to IEC 61537 Type II

Maintain electrical functions no

Material Stainless steel 1.4571  
Mounting perforation in base yes  
NATO hole pattern no  
Plate thickness 1,5 mm  
Rustproof steel, pickled no  
Side perforation yes  
Support spacing 1.5 m 2,7 kN/m  
Support spacing 2.0 m 2,1 kN/m  
Support spacing 2.5 m 1,47 kN/m  
Support spacing 3.0 m 0,8 kN/m  
Surface Bright, treated  
Type of connector, cable support system Click fastening  
Usable cross-section 238 cm<sup>2</sup>  
Usable cross-section 23800 mm<sup>2</sup>  
Wide-span version no  
Width 400 mm  
With cover no

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / SKSM 640 VA4571 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.