

**INDUSTRIAL COMPONENT DATA**

# BKRS 1130 FS 6061985 OBO BETTERMANN TRAY PASSABLE BKRS 1130 FS

Brand: OBO BETTERMANN | Manufacturer Part Number: BKRS 1130 FS



|                 |                                 |
|-----------------|---------------------------------|
| Manufacturer    | OBO BETTERMANN                  |
| MPN / Reference | BKRS 1130 FS                    |
| Catalog number  | 6061985                         |
| Category        | Cable tray/wide span cable tray |
| Minimum order   | 3 m.                            |
| Document ID     | EO-72E74CA13E                   |
| Generated       | 2026-07-31                      |

## Product Overview

TRAY PASSABLE BKRS 1130 FS

BKRS BKRS 1130 FS cable tray, walkable 110x300x3000 Steel, St, strip galvanized, DIN EN 10346

BKRS 110 FS walkable cable tray. Heavy and walkable BKRS cable tray system with 110 mm wing through hole. Magnetic insulation without cover 20 dB, with cover 50 dB.

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path      OBO BETTERMANN &gt; KTS cable support systems - OBO BETTERMANN

## Additional Product Information

Heavy-duty, walk-on cable tray system BKRS with base perforation, in 110 mm side height.

ETIM for 6061985 Cable tray, ladder and wire basket systems (EC000047)

Feature Name

Feature Value

Height (EF000040)

110 mm

Width (EF000008)

300 mm

Material thickness (EF000386)

2 mm

Length (EF001438)

3000 mm

Useful cross section (EF005140)

29600 mm<sup>2</sup>

With cover (EF007965)

No

Side perforation (EF001122)

No

Bottom perforation (EF004545)

Yes

NATO-mounting holes (EF006059)

No

Model (EF000010)

Coupler not included

Type of connector (EF000141)

Screwed

Suitable for circuit integrity (EF007806)

No

Material (EF002169)

Steel

Surface protection (EF000139)

Pre-galvanised

Weight (EF000167)

8.07 kg/m

Load test type according to IEC 61537 (EF015362)

Type II

Possible support spacing (EF017261)

1.5 m

Safe working load according to IEC 61537 with support spacing 1.5 m (EF017264)

3440

Safe working load according to IEC 61537 with support spacing 2.0 m (EF017265)

3330

Safe working load according to IEC 61537 with support spacing 2.5 m (EF017266)

2610

Safe working load according to IEC 61537 with support spacing 3.0 m (EF017267)

2080

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / BKRS 1130 FS with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.