


INDUSTRIAL COMPONENT DATA

STD-D0 RW3 6120042 OBO BETTERMANN POWER OUTLET
STD-D0 BLANCO3

Brand: OBO BETTERMANN | Manufacturer Part Number: STD-D0 RW3



Manufacturer	OBO BETTERMANN
MPN / Reference	STD-D0 RW3
Catalog number	6120042
Category	Socket outlet
Minimum order	1 Pcs
Document ID	EO-2B235E7240
Generated	2026-08-01

Product Overview

POWER OUTLET STD-D0 BLANCO3

0° electrical socket, triple STD-D0 RW3, ground connection 250V, 10/16A Polycarbonate, PC,
0° power socket, with earth, triple

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path OBO BETTERMANN > EGS device systems - OBO BETTERMANN

Additional Product Information

Protective contact socket triple 0°, with increased touch protection, with screwless terminals, 2-pin, 16 A, 250 V~, with connection terminals to IEC 60884-1.

ETIM for 6120042 Domestic wiring accessories and controls (EC000125)

Feature Name

Feature Value

Model (EF000010)

Socket outlet CEE 7/3 (type F)

With signal lamp (EF000198)

No

Number of modules (module system) (EF009573)

0

Number of socket outlets switchable (EF008814)

0

Imprint/indication (EF003823)
None

Connection type (EF000124)
Screwless terminal

With hinged lid (EF000117)
No

With enhanced contact protection (EF000389)
Yes

Label space/information surface (EF001035)
No

Colour (EF000007)
White

RAL-number (similar) (EF003882)
9010

Transparent (EF006243)
No

Lockable (EF000113)
No

Eject-mechanism (EF001051)
No

Insulated mounting (EF001588)
No

With function lighting (EF008861)
No

With orientation lighting (EF008862)
No

Over voltage protection (EF001332)
No

Fault current protection (EF001333)
No

With miniature fuse (EF006571)
No

Special power supply (EF001334)
EV006426

Mounting method (EF000003)
Trunking mounted

Type of fastening (EF002442)
Snap mounting (engagement)

Material (EF002169)
Plastic

Material quality (EF001257)
Other

Halogen free (EF000025)
Yes

With on/off switch (EF000488)
No

Rotated central insert (EF001331)

No
Nominal current (EF000001)
16 A
Nominal voltage (EF000002)
250 V
Suitable for degree of protection (IP) (EF006755)
Other
Device width (EF008808)
135 mm
Device height (EF008809)
45 mm
Device depth (EF008...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / STD-D0 RW3 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.