


**INDUSTRIAL COMPONENT DATA**

# 6207314 OBO BETTERMANN TRAY ESC BLIND SUN 110x750 FT

Brand: OBO BETTERMANN | Manufacturer Part Number: SLCS 1175 3 FT



|                 |                                     |
|-----------------|-------------------------------------|
| Manufacturer    | OBO BETTERMANN                      |
| MPN / Reference | SLCS 1175 3 FT                      |
| Catalog number  | 6207314                             |
| Category        | Cable ladder/wide span cable ladder |
| Minimum order   | 3 m.                                |
| Document ID     | EO-6672DC2DF5                       |
| Generated       | 2026-07-29                          |

## Product Overview

TRAY ESC BLIND SUN 110x750 FT

Cable ladder SLCS 110, 3 m C30 FT. Cable ladder with 110 mm side height with welded C30 profile rungs which are open in an upwards direction. Rolled side rail for reinforcement and as edge protection. Fastening to the bracket takes place using clamps, type LKS 40. The slot dimension of the frame is 16.5 mm and the appropriate clamp clip is type 2056. Magnetic shield insulation without cover 10 dB, with cover 15 dB.

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path OBO BETTERMANN > KTS cable support systems - OBO BETTERMANN

## Additional Product Information

CO2 Footprint (GWP) Cradle-to-Gate 14,6937 kg CO2e / 1 Meter

Colour zinc

Dimension 110x750x3000

Dimension B 750 mm

Fastening of rung Welded

Height 110 mm

Length 3000 mm

Maintain electrical functions no

Material Steel

Rail thickness 2 mm

Rung distance 300 mm

Rustproof steel, pickled no  
Side perforation yes  
Side rail version Flat profile  
Support spacing 2.0 m 3,5 kN/m  
Support spacing 3.0 m 1,9 kN/m  
Support spacing 4.0 m 1 kN/m  
Support spacing 5.0 m 0,8 kN/m  
Support spacing 6.0 m 0,25 kN/m  
Surface Hot-dip galvanised  
Usable cross-section 675 cm<sup>2</sup>  
Usable cross-section 67500 mm<sup>2</sup>  
Version of the rungs Profile unperforated  
Wide-span version no  
Width 750 mm

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / SLCS 1175 3 FT with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.