

INDUSTRIAL COMPONENT DATA

LCIS 620 3 FT 6209721 OBO BETTERMANN TRAY ESC PERF. SOLDD 60x200 FS

Brand: OBO BETTERMANN | Manufacturer Part Number: LCIS 620 3 FT



Manufacturer	OBO BETTERMANN
MPN / Reference	LCIS 620 3 FT
Catalog number	6209721
Category	Cable ladder/wide span cable ladder
Minimum order	3 m.
Document ID	EO-5593918E03
Generated	2026-07-28

Product Overview

TRAY ESC PERF. SOLDD 60x200 FS

LCIS 620 3 FT stair tray, Perforated step, welded 60x200x3000 Steel, St, Hot dip galvanized, DIN EN ISO 1461

Cable ladder LCIS 60, 3 m C30 FT. Cable ladder with a 60 mm side height with welded C30 profile rungs which are open in an upwards direction. Rolled side rail for reinforcement and as edge protection. Fastening to the bracket takes place using hold-down clamps, type LKS 40. The slot dimension of the rung is 16.5 mm and the appropriate clamp clip is type BS-H.... Magnetic shield insulation without cover 10 dB, with cover 15 dB.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	OBO BETTERMANN > KTS cable support systems - OBO BETTERMANN
--------------	---

Additional Product Information

CO2 Footprint (GWP) Cradle-to-Gate 6,2733 kg CO2e / 1 Meter

Colour zinc

Dimension 60x200x3000

Dimension B 200 mm

Fastening of rung Welded

Height 60 mm

Length 3000 mm

Maintain electrical functions no

Material Steel

Rail thickness 1,5 mm

Rung distance 300 mm
Rung slot dimension 17,00
Rustproof steel, pickled no
Side perforation yes
Side rail version Flat profile
Support spacing 1.5 m 3,3 kN/m
Support spacing 2.0 m 2 kN/m
Support spacing 2.5 m 1,3 kN/m
Support spacing 3.0 m 1 kN/m
Support spacing 3.5 m 0,78 kN/m
Support spacing 4.0 m 0,4 kN/m
Support spacing 4.5 m 0,3 kN/m
Support spacing 5.0 m 0,2 kN/m
Surface Hot-dip galvanised
Usable cross-section 80 cm²
Usable cross-section 8000 mm²
Version of the rungs Profile perforated
Wide-span version no
Width 200 mm

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / LCIS 620 3 FT with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.