

INDUSTRIAL COMPONENT DATA

7203843 OBO BETTERMANN PUTTY FILLER DRY-VMS-TE 2

Brand: OBO BETTERMANN | Manufacturer Part Number: VMS-TE 2



Manufacturer	OBO BETTERMANN
MPN / Reference	VMS-TE 2
Catalog number	7203843
Category	Fire partitioning
Minimum order	1 Pcs
Document ID	EO-E53698A3E1
Generated	2026-08-02

Product Overview

PUTTY FILLER DRY-VMS-TE 2

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path OBO BETTERMANN > BSS fire protection systems - OBO BETTERMANN

Additional Product Information

Dry compound in plastic container to mix with tap water. Makes a gas-tight and watertight seal of fire resistance class A-60 to IMO resolution A. 754(18). Including measuring cup.

The mixing ratio of water to powder is 1:2. The mixed compound is pumpable for approx. 45 minutes. The mixture is chemically hardened after 72 hours.

Stored in a dry and frost-free environment, the dry compound will keep for 3 years.

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / VMS-TE 2 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.