

## INDUSTRIAL COMPONENT DATA

# 7405077 OBO BETTERMANN SET P/MECAN UNI GES9-3BU7011

Brand: OBO BETTERMANN | Manufacturer Part Number: GES9-3B U 7011



|                 |                                              |
|-----------------|----------------------------------------------|
| Manufacturer    | OBO BETTERMANN                               |
| MPN / Reference | GES9-3B U 7011                               |
| Catalog number  | 7405077                                      |
| Category        | Installation box for underfloor-installation |
| Minimum order   | 1 Pcs                                        |
| Document ID     | EO-362897514E                                |
| Generated       | 2026-08-02                                   |

## Product Overview

### SET P/MECAN UNI GES9-3BU7011

GES9-3B service outlet with handle clamp. Service outlet with handle clamp for up to 12 individual Modul 45 devices in 3 UT4 universal supports, use in trunking systems and system floors for indoor use. Floor covering recess in the hinged cover pre-adjusted to 5 mm, if necessary adjustable to 10 mm. Service outlet with handle clamp, 3-compartment, for the installation of MT9 mounting support. Three type APMT5 cover plates can be installed. Floor covering recess in the hinged cover pre-adjusted to 5 mm, if necessary adjustable to 10 mm.

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                                                 |
|--------------|-----------------------------------------------------------------|
| Catalog path | OBO BETTERMANN > UFS Underfloor piping systems - OBO BETTERMANN |
|--------------|-----------------------------------------------------------------|

## Additional Product Information

Approvals VDE

Cable outlet version Swivellable cord outlet

Clamping range D, max. 76 mm

Clamping range D, min. 8 mm

CO2 Footprint (GWP) Cradle-to-Gate 6,2179 kg CO2e / 1 Piece

Colour Iron grey; RAL 7011

Device support to accept mounting boxes yes

Dimension 264x264x67

Dimension h 73 mm

Floor care Dry

Floor covering protection frame yes  
Floor covering thickness 5 mm  
Floor covering thickness max. 10 mm  
Floor height, min. 73 mm  
Frame version Carpet protection frame  
Heavy-duty version no  
Height 67 mm  
Installation depth 73 mm  
Installation system type UT4  
Length 264 mm  
Length of external dimensions 264 mm  
Length of installation dimensions 244 mm  
Material Polyamide  
Nominal size for device installation units 9  
Number of installable devices 12  
Number of mounting boxes 3  
Opening mechanism Handle  
Protection rating (IP) when unused IP40  
Protection rating (IP) when used IP20  
Protection rating IK code IK08  
Seal installation option no  
Suitable for cavity floor installation yes  
Suitable for raised floor installation yes  
Suitable for screed-covered underfloor ducts yes  
Suitable for screed-flush closed underfloor ducts no  
Suitable for underfloor ducts yes  
Suitable for wet care no  
Version for Square  
Vertical load, large area to 5,000 N  
Vertical load, small area to 3,000 N  
Wide external dimensions 264 mm  
Wide installation dimensions 244 mm  
Width 264 mm  
With floor covering recess yes

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / GES9-3B U 7011 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.