

INDUSTRIAL COMPONENT DATA

7405083 OBO BETTERMANN SET P/MECAN UNI GES9-3SU7011

Brand: OBO BETTERMANN | Manufacturer Part Number: GES9-3S U 7011



Manufacturer	OBO BETTERMANN
MPN / Reference	GES9-3S U 7011
Catalog number	7405083
Category	Installation box for underfloor-installation
Minimum order	1 Pcs
Document ID	EO-7F54761F2F
Generated	2026-08-02

Product Overview

SET P/MECAN UNI GES9-3SU7011

GES9-3S service outlet with locking slider. Service outlet with locking slider for up to 12 individual Modul 45 devices in 3 UT4 universal supports, use in trunking systems and system floors for indoor use. Floor covering recess in the hinged cover pre-adjusted to 5 mm, if necessary adjustable to 10 mm. Service outlet with locking slider, 3-compartment, for the installation of MT9 mounting support. Three type APMT5 cover plates can be installed. Floor covering recess in the hinged cover pre-adjusted to 5 mm, if necessary adjustable to 10 mm.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path OBO BETTERMANN > UFS Underfloor piping systems - OBO BETTERMANN

Additional Product Information

Approvals VDE
 Cable outlet version Swivellable cord outlet
 Clamping range D, max. 76 mm
 Clamping range D, min. 8 mm
 CO2 Footprint (GWP) Cradle-to-Gate 5,8492 kg CO2e / 1 Piece
 Colour Iron grey; RAL 7011
 Device support to accept mounting boxes yes
 Dimension 264x264x67
 Dimension h 73 mm
 Floor care Dry

Floor covering protection frame yes
Floor covering thickness 5 mm
Floor covering thickness max. 10 mm
Floor height, min. 73 mm
Frame version Carpet protection frame
Heavy-duty version no
Height 67 mm
Installation depth 73 mm
Installation system type UT4
Length 264 mm
Length of external dimensions 264 mm
Length of installation dimensions 244 mm
Material Polyamide
Nominal size for device installation units 9
Number of installable devices 12
Number of mounting boxes 3
Opening mechanism Locking slider
Protection rating (IP) when unused IP40
Protection rating (IP) when used IP20
Protection rating IK code IK08
Screed height, min. 73 mm
Seal installation option no
Suitable for cavity floor installation yes
Suitable for raised floor installation yes
Suitable for screed-covered underfloor ducts yes
Suitable for screed-flush closed underfloor ducts no
Suitable for underfloor ducts yes
Suitable for wet care no
Version for Square
Vertical load, large area to 5,000 N
Vertical load, small area to 3,000 N
Wide external dimensions 264 mm
Wide installation dimensions 244 mm
Width 264 mm
With floor covering recess yes

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / GES9-3S U 7011 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.