

INDUSTRIAL COMPONENT DATA

7409210 OBO BETTERMANN CAP AND MARCO SQ RKS2 4 VS 25

Brand: OBO BETTERMANN | Manufacturer Part Number: RKS2 4 VS 25



Manufacturer	OBO BETTERMANN
MPN / Reference	RKS2 4 VS 25
Catalog number	7409210
Category	Levelling cassette for duct mounting, raised and underfloor installation
Minimum order	1 Pcs
Document ID	EO-7C1AA09D8A
Generated	2026-08-01

Product Overview

CAP AND MARCO SQ RKS2 4 VS 25

Height-adjustable cassette with cord outlet, RKS2, stainless steel. Height-adjustable cassette of nominal size 4 with cord outlet for installation of accessories in dry-cleaned floors for indoor use. Height-adjustable cassette for cord outlet, 2-compartment. 2 APMT2 cover plates can be installed. For the installation of 2 UT3 universal supports for 4 individual installation devices with support ring/support clamp or 6 Modul 45 devices.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path OBO BETTERMANN > UFS Underfloor piping systems - OBO BETTERMANN

Additional Product Information

Approvals VDE
 Cable outlet version Swivellable cord outlet
 CO2 Footprint (GWP) Cradle-to-Gate 15,6556 kg CO2e / 1 Piece
 Decouplable no
 Device support to accept mounting boxes yes
 Dimension 200x200mm
 Dimension h 110 mm
 Floor care Dry
 Floor covering thickness 25 mm
 Floor height, max. 155 mm
 Floor height, min. 110 mm

Heavy-duty version no
Height-adjustment range, max. 155 mm
Height-adjustment range, min. 110 mm
Installation depth 110 mm
Installation system type UT3
Length 199 mm
Length of installation dimensions 201 mm
Material Stainless steel 1.4301
Nominal size for device installation units 4
Number of cable outlets 1
Number of installable devices 6
Number of mounting boxes 2
Protection rating (IP) when unused IP40
Protection rating (IP) when used IP20
Protection rating IK code IK10
Suitable for cavity floor installation yes
Suitable for raised floor installation yes
Version for Square
Vertical load, large area to 5,000 N
Vertical load, small area to 3,000 N
Wide installation dimensions 201 mm
Width 199 mm

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / RKS2 4 VS 25 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.