

**INDUSTRIAL COMPONENT DATA**

# 7409210 OBO BETTERMANN CAP AND MARCO SQ RKS2 4 VS 25

Brand: OBO BETTERMANN | Manufacturer Part Number: RKS2 4 VS 25



|                 |                                                                          |
|-----------------|--------------------------------------------------------------------------|
| Manufacturer    | OBO BETTERMANN                                                           |
| MPN / Reference | RKS2 4 VS 25                                                             |
| Catalog number  | 7409210                                                                  |
| Category        | Levelling cassette for duct mounting, raised and underfloor installation |
| Minimum order   | 1 Pcs                                                                    |
| Document ID     | EO-7C1AA09D8A                                                            |
| Generated       | 2026-08-02                                                               |

## Product Overview

### CAP AND MARCO SQ RKS2 4 VS 25

Height-adjustable cassette with cord outlet, RKS2, stainless steel. Height-adjustable cassette of nominal size 4 with cord outlet for installation of accessories in dry-cleaned floors for indoor use. Height-adjustable cassette for cord outlet, 2-compartment. 2 APMT2 cover plates can be installed. For the installation of 2 UT3 universal supports for 4 individual installation devices with support ring/support clamp or 6 Modul 45 devices.

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path OBO BETTERMANN > UFS Underfloor piping systems - OBO BETTERMANN

## Additional Product Information

Approvals VDE  
Cable outlet version Swivellable cord outlet  
CO2 Footprint (GWP) Cradle-to-Gate 15,6556 kg CO2e / 1 Piece  
Decouplable no  
Device support to accept mounting boxes yes  
Dimension 200x200mm  
Dimension h 110 mm  
Floor care Dry  
Floor covering thickness 25 mm  
Floor height, max. 155 mm  
Floor height, min. 110 mm

Heavy-duty version no  
Height-adjustment range, max. 155 mm  
Height-adjustment range, min. 110 mm  
Installation depth 110 mm  
Installation system type UT3  
Length 199 mm  
Length of installation dimensions 201 mm  
Material Stainless steel 1.4301  
Nominal size for device installation units 4  
Number of cable outlets 1  
Number of installable devices 6  
Number of mounting boxes 2  
Protection rating (IP) when unused IP40  
Protection rating (IP) when used IP20  
Protection rating IK code IK10  
Suitable for cavity floor installation yes  
Suitable for raised floor installation yes  
Version for Square  
Vertical load, large area to 5,000 N  
Vertical load, small area to 3,000 N  
Wide installation dimensions 201 mm  
Width 199 mm

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / RKS2 4 VS 25 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.