


INDUSTRIAL COMPONENT DATA

RКСN2 9 MS 20 7409212 OBO BETTERMANN CAP AND MARCO SQ RКСN2 9 MS 20

Brand: OBO BETTERMANN | Manufacturer Part Number: RКСN2 9 MS 20



Manufacturer	OBO BETTERMANN
MPN / Reference	RКСN2 9 MS 20
Catalog number	7409212
Category	Levelling cassette for duct mounting, raised and underfloor installation
Minimum order	1 Pcs
Document ID	EO-A5890D7FD8
Generated	2026-07-27

Product Overview

CAP AND MARCO SQ RКСN2 9 MS 20

RКСN2 9 MS 20 square cover and frame set, with cable outlet 243x243mm Brass, CuZn, Height-adjustable cassette with cord outlet, RКСN, brass. Height-adjustable cassette of nominal size 9 with cord outlet, for the installation of accessories in dry-cleaned floors indoors. For the installation of 3 UT4 universal supports for 9 individual installation devices with support ring/support clamp or 6 Modul 45® devices. Height-adjustable square cassette, 3-compartment, with cord outlet of nominal size 9 for the installation of accessories. Suitable for the use in trunking systems, raised and cavity floors in dry- and wet-cleaned floors in indoor areas. Three cover plates APMT5 can be installed. Suitable only for smooth floor coverings.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	OBO BETTERMANN > UFS Underfloor piping systems - OBO BETTERMANN
--------------	---

Additional Product Information

Approvals VDE

Cable outlet version Swivellable cord outlet

CO2 Footprint (GWP) Cradle-to-Gate 14,0497 kg CO2e / 1 Piece

Decouplable no

Device support to accept mounting boxes yes

Dimension 243x243mm

Dimension h 105 mm

Floor care Dry

Floor covering thickness 20 mm
Floor height, max. 150 mm
Floor height, min. 105 mm
Heavy-duty version no
Height-adjustment range, max. 150 mm
Height-adjustment range, min. 105 mm
Installation depth 105 mm
Installation system type UT4
Length of installation dimensions 244 mm
Material Brass
Nominal size 350 mm
Nominal size for device installation units 9
Number of cable outlets 1
Number of installable devices 12
Number of mounting boxes 3
Protection rating (IP) when unused IP40
Protection rating (IP) when used IP20
Protection rating IK code IK10
Suitable for cavity floor installation yes
Suitable for raised floor installation yes
Version for Square
Vertical load, large area to 5,000 N
Vertical load, small area to 3,000 N
Wide installation dimensions 244 mm
ETIM for 7409212 Underfloor trunking and floor boxes (EC002603)
Feature Name
Feature Value
Nominal dimension (EF000132)
350 mm
Min. built-in depth (EF005027)
105 mm
Levelling height (EF007999)
105 mm
Floor maintenance (EF004546)
Dry
Model (EF000010)
Square
Material (EF002169)
Brass
Number of conduit outlets (EF004424)
1
Type of conduit outlet (EF004474)
Swivelling
Chassis part for device cups (EF004750)
Yes
Length built-in dimension (EF004875)
244 mm

Width built-in dimension (EF004566)

244 mm

Num...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / RKS2 9 MS 20 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.