

INDUSTRIAL COMPONENT DATA

7409218 OBO BETTERMANN CAP AND MARCO SQ RKS2 9 VS 20

Brand: OBO BETTERMANN | Manufacturer Part Number: RKS2 9 VS 20



Manufacturer	OBO BETTERMANN
MPN / Reference	RKS2 9 VS 20
Catalog number	7409218
Category	Levelling cassette for duct mounting, raised and underfloor installation
Minimum order	1 Pcs
Document ID	EO-69713352AE
Generated	2026-08-01

Product Overview

CAP AND MARCO SQ RKS2 9 VS 20

Height-adjustable cassette with cord outlet, RKS2, stainless steel. Height-adjustable cassette of nominal size 9 with cord outlet for installation of accessories in dry-care floors for indoor use. For the installation of 3 UT4 universal supports for 9 individual installation devices with support ring/support clamp or 12 Modul 45® devices. Height-adjustable square cassette, 3-compartment, with cord outlet of nominal size 9 for the installation of accessories. Cassette suitable for the use in trunking systems, raised and cavity floors in dry- and wet-cleaned floors in indoor areas. Suitable only for smooth floor coverings. Three cover plates APMT5 can be installed.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path OBO BETTERMANN > UFS Underfloor piping systems - OBO BETTERMANN

Additional Product Information

Approvals VDE
 Cable outlet version Swivellable cord outlet
 CO2 Footprint (GWP) Cradle-to-Gate 20,7553 kg CO2e / 1 Piece
 Decouplable no
 Device support to accept mounting boxes yes
 Dimension 243x243mm
 Dimension h 105 mm
 Floor care Dry
 Floor covering thickness 20 mm

Floor height, max. 150 mm
Floor height, min. 105 mm
Heavy-duty version no
Height-adjustment range, max. 150 mm
Height-adjustment range, min. 105 mm
Installation depth 105 mm
Installation system type UT4
Length 243 mm
Length of installation dimensions 244 mm
Material Stainless steel 1.4301
Nominal size 350 mm
Nominal size for device installation units 9
Number of cable outlets 1
Number of installable devices 12
Number of mounting boxes 3
Protection rating (IP) when unused IP40
Protection rating (IP) when used IP20
Protection rating IK code IK10
Suitable for cavity floor installation yes
Suitable for raised floor installation yes
Version for Square
Vertical load, large area to 5,000 N
Vertical load, small area to 3,000 N
Wide installation dimensions 244 mm
Width 243 mm

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / RKS2 9 VS 20 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.